



Ultra Duty Dump Trailers (14,000 lbs. GVWR)



Standard Features

- Tandem 7,000 lbs. Drop Axles
- 16" Radial Tires
- Electric Brakes on Both Axles
- Slipper Suspension
- Barn Doors with Cam Lock
- Two-way Gate included with 6.5' Models
- 12,000 lbs. Jack
- 2-5/16" Adjustable Coupler or 3" Lunette Eye
- Lockable Toolbox
- Interstate Extreme Cycle Battery
- 3,000 psi Hydraulic Power Pack, 20' Hand Remote
- 5" Hydraulic Cylinder & Scissor Hoist
- 6" Hydraulic Cylinder & Scissor Hoist - 16' Models
- Shielded Tarp & Roller, (4) Heavy Duty D-Rings
- Spare Tire Mount
- Powder Coated
- Sealed Beam L.E.D. Lights and Harness System
- Transport Canada & DOT Approved Lighting

Standard Sizes

Size	Model
6' x 10'	DT610-14K
6' x 12'	DT612-14K
6.5' x 12'	DT6.512-14K
6.5' x 14'	DT6.514-14K
6.5' x 16'	DT6.516-14K

Standard Specifications

Tire Size	ST235/80R16 LRE
Deck Height	25"
Tongue Length	52"
Box Height	33" (including 11" Plank)
GVWR	14,000 lbs.

Options

- Spare Tire
- Ramp Kit
- Torsion Axles
- Two-way Gate (included with 6.5' Models)
- Additional D-Rings
- Hydraulic Brakes
- Aluminum Wheels
- 48" High Sides
- 58" High Sides
- Heavy Gauge Floor

Request more information: **TEL** 1-877-565-3714 **EMAIL** info@canadatrailers.com