



CANADA TRAILERS

Single Axle Steel Side Utility Trailers



Standard Features & Specifications

GVWR:	3K: 1,356 kg (2,990 lbs) 3.5K: 1,587 kg (3,500 lbs) 5K: 2,267 kg (5,000 lbs)
Axle(s) & Suspension:	3K & 3.5K: (1) 3,500 lb Axle w/Easy Lube Spindles, Double Eye Spring Suspension 5K: (1) 5,200 lb Axle w/ same
Tires:	3K & 3.5K: ST205/75R15 LRC Radial 5K: ST225/75R15 LRE Radial
Coupler:	2" A-Frame Coupler
Jack:	2,000 lbs A-Frame Jack
Deck Height:	17"
Sides:	15" Solid Steel + 3" Tie Rail
Ramp:	4' Straight Ramp w/ Mesh
Floor:	Pressure Treated Wood
Tongue Length:	5' Models : 42" 6' Models : 46" 7' Models : 48"
Tie Downs:	(4) Welded In D-Rings
Spare Tire Mount:	Front of Bed, Upright
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	3K: Sealed Harness & 4 Way Flat Plug 3.5K & 5K: 7 Way RV Plug
Finish:	Powder Coat – Matte Black

Models

UT58-3K	60.5" x 98"	422 kg (931 lbs)
UT510-3K	60.5" x 122"	466 kg (1,028 lbs)
UT512-3K	60.5" x 146"	516 kg (1,138 lbs)
UT514-3K	60.5" x 170"	555 kg (1,224 lbs)
UT610-3K	72" x 122"	521 kg (1,148 lbs)
UT612-3K	72" x 146"	578 kg (1,274 lbs)
UT712-3.5K	82" x 146"	635 kg (1,400 lbs)
UT714-3.5K	82" x 170"	678 kg (1,494 lbs)
UT712-5K	82" x 146"	748 kg (1,650 lbs)
UT714-5K	82" x 170"	791 kg (1,744 lbs)

Popular Options

Bifold Ramp (5ft & 6ft only)	Electric Brakes
Additional D-Rings	Aluminum Wheels
5K Axle	Galvanize Trailer

Dealer Information & Pricing

