



CANADA TRAILERS

Gooseneck XD Series Trailers



Standard Features & Specifications

GVWR:	24KD: 11,757 kg (25,920 lbs) 30KD: 13,636 kg (30,000 lbs)
Axle(s) & Suspension:	24KD: (2) 12,000 lb Axles, Dually 30KD: (2) 15,000 lb Axles, Dually w/Oil Bath Hubs, Slipper Spring Suspension
Tires:	24KD: ST235/80R16 LRE Radial 30KD: ST215/75R15 LRH Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable Gooseneck Coupler
Jack:	12,000 lb 2 Speed Jacks
Ramps:	5' Full Width Ramps
Deck Height:	36"
Frame:	12" @ 22 lbs. Wide Flange I-Beam Frame. Torque Tube. Crossmembers every 16". HD 1/4" Plate over Axles.
Floor:	Pressure Treated Wood
Gooseneck Length:	9'
Beavertail:	5' Angle Iron Beavertail
Tie Downs:	Stake Pockets & Rub Rails
Side Steps:	On Both Sides
Winch Track:	Driver's Side
Spare Tire Mount:	On Gooseneck
Loading Lights:	Rear Facing w/ Remote On/Off
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

GNXD32-24KD	102" x 384"	4,080 kg (8,978 lbs)
GNXD35-24KD	102" x 420"	4,307 kg (9,476 lbs)
GNXD40-24KD	102" x 480"	4,750 kg (10,450 lbs)
GNXD32-30KD	102" x 384"	4,217 kg (9,278 lbs)
GNXD35-30KD	102" x 420"	4,444 kg (9,776 lbs)
GNXD40-30KD	102" x 480"	4,886 kg (10,750 lbs)

Popular Options

King Pin	Hydraulic Brakes
Spare Tire	

Dealer Information & Pricing





CANADA TRAILERS

Equipment Trailers 102" Wide



Standard Features & Specifications

GVWR:	10K: 4,899 kg (10,800 lbs) 14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs)
Axle(s) & Suspension:	10K: (2) 5,200 lb Axles 14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	10K: ST225/75R15 LRE Radial 14K: ST235/80R16 LRE Radial 21KTR: ST235/80R16 LRE Radial
Brakes:	Electric on all Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lbs Drop Leg Jack
Fenders:	HD Drive Over Fenders
Deck Height:	24"
Beavertail:	2' with Wood Floor
Ramps:	5' Spring Assisted Up-right Ramps
Floor:	Pressure Treated Wood
Tongue Length:	52"
Tie Downs:	Stake Pockets & Rub Rails
Spare Tire Mount:	Passenger Side- Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

CE714-10K 102"	102" x 168"	1,278 kg (2,812 lbs)
CE716-10K 102"	102" x 192"	1,365 kg (3,004 lbs)
CE718-10K 102"	102" x 216"	1,471 kg (3,237 lbs)
CE720-10K 102"	102" x 240"	1,561 kg (3,435 lbs)
CE714-14K 102"	102" x 168"	1,349 kg (2,968 lbs)
CE716-14K 102"	102" x 192"	1,436 kg (3,160 lbs)
CE718-14K 102"	102" x 216"	1,542 kg (3,393 lbs)
CE720-14K 102"	102" x 240"	1,632 kg (3,591 lbs)
CE722-14K 102"	102" x 264"	1,713 kg (3,769 lbs)
CE724-14K 102"	102" x 288"	1,805 kg (3,971 lbs)
CE720-21KTR 102"	102" x 240"	1,980 kg (4,356 lbs)
CE722-21KTR 102"	102" x 264"	2,042 kg (4,493 lbs)
CE724-21KTR 102"	102" x 288"	2,115 kg (4,653 lbs)

Popular Options

Spare Tire	16K (2) 8K Axles
Lockable Steel Toolbox	Aluminum Wheels
4' Beaver Tail	Galvanize Trailer
5' Extra Wide Ramps	Straight Deck
Hydraulic Brakes	Gooseneck

Dealer Information & Pricing





CANADA TRAILERS

102" Wide Hydraulic Full Deck Tilt Trailers



Standard Features & Specifications

GVWR:	10K: 4,899 kg (10,800 lbs) 14K: 6,350 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs)
Axle(s) & Suspension:	10K: (2) 6,000 lb Axles 14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	10K: ST225/75R15 LRE Radial 14K: ST235/80R16 LRE Radial 21KTR: ST235/80R16 LRE Radial
Brakes:	Electric on Both Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lbs Drop Leg Jack
Fenders:	HD Drive Over Fenders
Deck Height:	24"
Tilt Features:	Electric over Hydraulic Full Tilt 3" Hydraulic Cylinder Interstate Extreme Cycle Battery Lockable Steel Toolbox
Winch Plate:	Yes
Floor:	Pressure Treated Wood
Tongue Length:	52"
Tie Downs:	Stake Pockets & Rub Rails
Spare Tire Mount:	Passenger Side- Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

ETL718-10K 102"	102" x 216"	1,331 kg (2,929 lbs)
ETL720-10K 102"	102" x 240"	1,419 kg (3,121 lbs)
ETL718-14K 102"	102" x 216"	1,471 kg (3,237 lbs)
ETL720-14K 102"	102" x 240"	1,561 kg (3,435 lbs)
ETL722-14K 102"	102" x 264"	1,802 kg (3,965 lbs)
ETL724-14K 102"	102" x 288"	1,959 kg (4,309 lbs)
ETL724-21KTR 102"	102" x 288"	2,105 kg (4,631 lbs)

Popular Options

Spare Tire	Aluminum Wheels
Hydraulic Brakes	Gooseneck
D-Rings	Galvanize Trailer
16K (2) 8K Axles	

Dealer Information & Pricing





CANADA TRAILERS

Gooseneck Full Deck Tilt Trailers 102" Wide



Standard Features & Specifications

GVWR:	10K: 4,899 kg (10,800 lbs) 14K: 6,350 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs)
Axle(s) & Suspension:	10K: (2) 6,000 lb Axles 14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	10K: ST225/75R15 LRE Radial 14K: ST235/80R16 LRE Radial 21KTR: ST235/80R16 LRE Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable Gooseneck Coupler
Jack:	12,000 lbs Drop Leg Jack
Fenders:	HD Drive Over Fenders
Deck Height:	24"
Tilt Features:	Electric over Hydraulic Full Tilt 3" Hydraulic Cylinder Interstate Extreme Cycle Battery Lockable Steel Toolbox
Winch Plate:	Yes
Floor:	Pressure Treated Wood & Steel
Gooseneck Length:	9'
Tie Downs:	Stake Pockets & Rub Rails
Spare Tire Mount:	Passenger Side- Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard

Models

GNETL718-10K 102"	102"x 216"	1,618 kg (3,560 lbs)
GNETL720-10K 102"	102"x 240"	1,737 kg (3,822 lbs)
GNETL718-14K 102"	102"x 216"	1,758 kg (3,868 lbs)
GNETL720-14K 102"	102"x 240"	1,880 kg (4,136 lbs)
GNETL722-14K 102"	102"x 264"	2,153 kg (4,736 lbs)
GNETL724-14K 102"	102"x 288"	2,341 kg (5,150 lbs)
GNETL724-21KTR 102"	102"x 288"	2,487 kg (5,472 lbs)

Popular Options

Spare Tire	16K (2) 8K Axles
Hydraulic Brakes	Aluminum Wheels
D-Rings	Galvanize Trailer

Dealer Information & Pricing





CANADA TRAILERS

Ultra Duty Dump Trailers w/ Drop Sides



Standard Features & Specifications

GVWR:	14K: 6,858 kg (15,120 lbs) 16K: 7,855 kg (17,280 lbs) 21KTR: 10,287 kg (22,680 lbs) 24KD: 11,757 kg (25,920 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles 16K: (2) 8,000 lb Axles 21KTR: (3) 7000 lb Axles w/Easy Lube Spindles, Slipper Spring 24KD: (2) 12,000 lb Axles, Dually w/Oil Bath Hubs, Slipper Spring Suspension
Tires:	ST235/80R16 LRE Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lb Drop Leg Jack
Deck Height:	29"
Sides:	Drop Sides
Doors:	Barn Doors with Cam Lock. Two Way Gate.
Load Cover:	Shielded Tarp & Roller
Hoist Features:	3,000 psi Hydraulic Power Pack, 20' Hand Remote and Wireless Remote. 6" Hydraulic Cylinder, with Scissor Hoist. Interstate Extreme Cycle Battery and Plug in Charger. Lockable Steel Toolbox.
Floor:	Steel
Tongue Length:	58"
Tie Downs:	(6) Heavy Duty Welded In D-Rings

Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard

Models

DT814-14K	94" x 166.5"	2,402 kg (5,295 lbs)
DT816-14K	94" x 190.5"	2,742 kg (6,044 lbs)
DT816-16K	94" x 190.5"	2,969 kg (6,544 lbs)
DT816-21KTR	94" x 190.5"	2,901 kg (6,396 lbs)
DT816-24KD	94" x 190.5"	3,083 kg (6,796 lbs)

Popular Options

Spare Tire	Hydraulic Brakes
Additional D-Rings	Aluminum Wheels
Torsion Axle (N/A on 16K & 24KD)	Galvanize Trailer

Dealer Information & Pricing

