



CANADA TRAILERS



Canada Trailers Manufacturing Limited

11918 Imperial Road, Hwy. 73
Aylmer Ontario
N5H 2R3

Phone: 519-765-1717

Fax: 519-765-1725

www.canadatrailers.com



CANADA TRAILERS

Table of Contents

| Trailer Model | Page # |
|--|--------|
| Single Axle Steel Side Utility Trailers | 1 |
| Single Axle Flat Deck Utility Trailers | 2 |
| Tandem Axle Steel Side Landscape/Utility Trailers | 3 |
| H.D. Tandem Axle Steel Side Landscape/Utility Trailers | 4 |
| Car Trailers | 5 |
| Equipment Trailers | 6 |
| Low Incline Scissor Lift Trailers | 7 |
| Single Axle Gravity Tilt Trailers | 8 |
| Gravity Tilt Trailers w/ 4' Stationary Deck | 9 |
| Electric Hydraulic Full Deck Tilt Trailers | 10 |
| Deck Over Hydraulic Power Tilt Trailers | 11 |
| Heavy Duty Dump Trailers | 12 |
| Ultra Duty Dump Trailers | 13 |
| Gooseneck Dump Trailers | 14 |
| Straight Deck Pintle Series Trailers | 15 |
| Straight Deck Gooseneck Series Trailers | 16 |
| Beavertail Deck Over Pintle Series Trailers | 17 |
| Premium Pintle Series Trailers | 18 |
| Premium Gooseneck Series Trailers | 19 |



CANADA TRAILERS

Single Axle Steel Side Utility Trailers



Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 3K: 1,356 kg (2,990 lbs) 3.5K: 1,587 kg (3,500 lbs) 5K: 2,267 kg (5,000 lbs) |
| Axle(s) & Suspension: | 3K & 3.5K: (1) 3,500 lb Axle w/Easy Lube Spindles, Double Eye Spring Suspension 5K: (1) 5,200 lb Axle w/ same |
| Tires: | 3K & 3.5K: ST205/75R15 LRC Radial 5K: ST225/75R15 LRE Radial |
| Brakes: | Electric |
| Coupler: | 2" A-Frame Coupler |
| Jack: | 3 & 3.5K: 2,000 lbs A-Frame Jack 5K: 5,000 lbs A-Frame Jack |
| Deck Height: | 17" |
| Sides: | 15" Solid Steel + 3" Tie Rail |
| Ramp: | 3 & 3.5K: 4' Straight Ramp w/ Mesh 5K: Spring Assisted Ramps |
| Floor: | Pressure Treated Wood |
| Tongue Length: | 5' Models : 42" 6' Models : 46" 7' Models : 48" |
| Tie Downs: | (4) Welded In D-Rings |
| Spare Tire Mount: | Front of Bed, Upright |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | 3K: Sealed Harness & 4 Way Flat Plug 3.5K & 5K: 7 Way RV Plug |
| Finish: | Powder Coat – Matte Black |


Models

| | | |
|------------|--------------|--------------------|
| UT58-3K | 60.5" x 98" | 422 kg (931 lbs) |
| UT510-3K | 60.5" x 122" | 466 kg (1,028 lbs) |
| UT512-3K | 60.5" x 146" | 516 kg (1,138 lbs) |
| UT514-3K | 60.5" x 170" | 555 kg (1,224 lbs) |
| UT610-3K | 72" x 122" | 521 kg (1,148 lbs) |
| UT612-3K | 72" x 146" | 578 kg (1,274 lbs) |
| UT712-3.5K | 82" x 146" | 635 kg (1,400 lbs) |
| UT714-3.5K | 82" x 170" | 678 kg (1,494 lbs) |
| UT712-5K | 82" x 146" | 748 kg (1,650 lbs) |
| UT714-5K | 82" x 170" | 791 kg (1,744 lbs) |

Popular Options

| | |
|------------------------------|-------------------|
| Bifold Ramp (5ft & 6ft only) | Galvanize Trailer |
| Additional D-Rings | Aluminum Wheels |
| 5K Axle | |

Dealer Information & Pricing





CANADA TRAILERS

Single Axle Flat Deck Utility Trailers



Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 3K: 1,356 kg (2,990 lbs) 3.5K: 1,587 kg (3,500 lbs) |
| Axle(s) & Suspension: | (1) 3,500 lb Axle w/Easy Lube Spindles Double Eye Spring Suspension |
| Tires: | 3K & 3.5K: ST205/75R15 LRC Radial |
| Coupler: | 2" A-Frame Coupler |
| Jack: | 2,000 lbs A-Frame Jack |
| Deck Height: | 17" |
| Ramps: | 4' Pull Out Ramps |
| Floor: | Pressure Treated Wood |
| Tongue Length: | 5' Models : 42" 6' Models : 46" 7' Models : 48" |
| Tie Downs: | Stake Pockets (4) Welded In D-Rings |
| Spare Tire Mount: | Passenger Side - Removeable |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | 3K: Sealed Harness & 4 Way Flat Plug 3.5K: 7 Way RV Plug |
| Finish: | Powder Coat – Matte Black |


Models

| | | |
|-----------|--------------|--------------------|
| F58-3K | 60.5" x 96" | 357 kg (788 lbs) |
| F510-3K | 60.5" x 120" | 390 kg (860 lbs) |
| F512-3K | 60.5" x 144" | 429 kg (945 lbs) |
| F514-3K | 60.5" x 168" | 464 kg (1,024 lbs) |
| F610-3K | 72" x 120" | 431 kg (951 lbs) |
| F612-3K | 72" x 144" | 475 kg (1,048 lbs) |
| F712-3.5K | 82" x 144" | 543 kg (1,197 lbs) |
| F714-3.5K | 82" x 168" | 671 kg (1,479 lbs) |

Popular Options

| | |
|--------------------|-------------------|
| Spare Tire | Electric Brakes |
| Additional D-Rings | Aluminum Wheels |
| 5K Axle | Galvanize Trailer |
| Torsion Axle | |

Dealer Information & Pricing





Tandem Axle Steel Side Landscape/Utility Trailers



Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 3,429 kg (7,560 lbs) |
| Axle(s) & Suspension: | (2) 3,500 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| Tires: | ST205/75R15 LRC Radial |
| Brakes: | Electric on Both Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | 2,000 lbs A-Frame Jack |
| Fenders: | HD Fenders |
| Deck Height: | 19" |
| Sides: | 15" Solid Steel + 3" Tie Rail |
| Ramps: | 4' Split Ramps w/ Mesh |
| Floor: | Pressure Treated Wood |
| Tongue Length: | 53" |
| Tie Downs: | Stake Pockets Welded In D-Rings |
| Spare Tire Mount: | Front of Bed, Upright |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|----------|------------|----------------------|
| UT712-7K | 82" x 145" | 850 kg (1,874 lbs) |
| UT714-7K | 82" x 169" | 903 kg (1,991 lbs) |
| UT716-7K | 82" x 193" | 957 kg (2,109 lbs) |
| UT718-7K | 82" x 217" | 1,008 kg (2,223 lbs) |
| UT720-7K | 82" x 241" | 1,068 kg (2,354 lbs) |

Popular Options

| | |
|------------------------|--------------------|
| Spare Tire | Torsion Axles |
| Lockable Steel Toolbox | Additional D-Rings |
| 7000 lbs Drop Leg Jack | Aluminum Wheels |
| Rear Stabilizers | Galvanize Trailer |
| Side ATV Ramps | |

Dealer Information & Pricing





CANADA TRAILERS

H.D. Tandem Axle Steel Side Landscape/Utility Trailers



Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 10K: 4,899 kg (10,800 lbs) 14K: 6,858 kg (15,120 lbs) |
| Axle(s) & Suspension: | 10K: (2) 6,000 lb Axles 14K: (2) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| Tires: | 10K: ST225/75R15 LRE Radial 14K: ST235/80R16 LRE Radial |
| Brakes: | Electric on Both Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | 12,000 lbs Drop Leg Jack |
| Fenders: | HD Fenders |
| Deck Height: | 20" |
| Sides: | 15" Solid Steel + 3" Tie Rail |
| Ramps: | 5' Heavy Duty Spring Assisted Split Ramps w/ Mesh |
| Floor: | Pressure Treated Wood |
| Tongue Length: | 53" |
| Tie Downs: | Stake Pockets Welded In D-Rings |
| Spare Tire Mount: | Front of Bed, Upright |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|-----------|------------|----------------------|
| UT716-10K | 82" x 193" | 1,146 kg (2,526 lbs) |
| UT718-10K | 82" x 217" | 1,201 kg (2,648 lbs) |
| UT720-10K | 82" x 241" | 1,261 kg (2,780 lbs) |
| UT722-10K | 82" x 265" | 1,314 kg (2,897 lbs) |
| UT724-10K | 82" x 288" | 1,367 kg (3,014 lbs) |
| UT716-14K | 82" x 193" | 1,217 kg (2,682 lbs) |
| UT718-14K | 82" x 217" | 1,272 kg (2,804 lbs) |
| UT720-14K | 82" x 241" | 1,331 kg (2,935 lbs) |
| UT722-14K | 82" x 265" | 1,385 kg (3,053 lbs) |
| UT724-14K | 82" x 288" | 1,438 kg (3,171 lbs) |

Popular Options

| | |
|------------------------|--------------------|
| Spare Tire | Torsion Axles |
| Lockable Steel Toolbox | Additional D-Rings |
| Hydraulic Brakes | Aluminum Wheels |
| Rear Stabilizers | Galvanize Trailer |

Dealer Information & Pricing





CANADA TRAILERS

Car Trailers



Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 3,429 kg (7,560 lbs) |
| Axle(s) & Suspension: | (2) 3,500 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| Tires: | ST205/75R15 LRC Radial |
| Brakes: | Electric on Both Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | 2,000 lbs A-Frame Jack |
| Fenders: | HD Fenders |
| Deck Height: | 23" |
| Sides: | 2' with Wood Floor |
| Ramps: | 4' Ramps – Stored Under Deck |
| Floor: | Pressure Treated Wood |
| Tongue Length: | 53" |
| Tie Downs: | Stake Pockets |
| Spare Tire Mount: | Passenger Side- Removeable |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|----------|------------|----------------------|
| CE714-7K | 82" x 168" | 871 kg (1,920 lbs) |
| CE716-7K | 82" x 192" | 923 kg (2,035 lbs) |
| CE718-7K | 82" x 216" | 974 kg (2,147 lbs) |
| CE720-7K | 82" x 240" | 1,036 kg (2,285 lbs) |

Popular Options

| | |
|-----------------------------------|-------------------|
| Spare Tire | Torsion Axles |
| Lockable Steel Toolbox | Straight Deck |
| 7000 lbs Drop Leg Jack | Aluminum Wheels |
| 4' Beaver Tail | Galvanize Trailer |
| 5' Spring Assisted Up-right Ramps | Hydraulic Brakes |

Dealer Information & Pricing





Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 10K: 4,899 kg (10,800 lbs) 14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs) |
| Axle(s) & Suspension: | 10K: (2) 5,200 lb Axles 14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| Tires: | 10K: ST225/75R15 LRE Radial 14K & 21KTR: ST235/80R16 LRE Radial |
| Brakes: | Electric on all Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | 12,000 lbs Drop Leg Jack |
| Fenders: | HD Fenders |
| Deck Height: | 24" |
| Beavertail: | 2' with Wood Floor |
| Ramps: | 5' Spring Assisted Up-right Ramps |
| Floor: | Pressure Treated Wood |
| Tongue Length: | 52" |
| Tie Downs: | Stake Pockets & Rub Rails |
| Spare Tire Mount: | Passenger Side- Removeable |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|-------------|------------|----------------------|
| CE714-10K | 80" x 168" | 1,090 kg (2,403 lbs) |
| CE716-10K | 80" x 192" | 1,150 kg (2,536 lbs) |
| CE718-10K | 80" x 216" | 1,230 kg (2,711 lbs) |
| CE720-10K | 80" x 240" | 1,293 kg (2,850 lbs) |
| CE714-14K | 80" x 168" | 1,161 kg (2,559 lbs) |
| CE716-14K | 80" x 192" | 1,221 kg (2,692 lbs) |
| CE718-14K | 80" x 216" | 1,300 kg (2,867 lbs) |
| CE720-14K | 80" x 240" | 1,363 kg (3,005 lbs) |
| CE722-14K | 80" x 264" | 1,418 kg (3,126 lbs) |
| CE724-14K | 80" x 288" | 1,488 kg (3,270 lbs) |
| CE720-21KTR | 83" x 240" | 1,710 kg (3,771 lbs) |
| CE722-21KTR | 83" x 264" | 1,746 kg (3,850 lbs) |
| CE724-21KTR | 83" x 288" | 1,793 kg (3,952 lbs) |

Popular Options

| | |
|------------------------|-------------------|
| Spare Tire | Torsion Axles |
| Lockable Steel Toolbox | 16K (2) 8K Axles |
| 4' Beaver Tail | Aluminum Wheels |
| 5' HD Landscape Ramps | Galvanize Trailer |
| Hydraulic Brakes | Straight Deck |
| Gooseneck | |

Dealer Information & Pricing





CANADA TRAILERS

Low Incline Scissor Lift Trailers



Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 10K: 4,899 kg (10,800 lbs) 14K: 6,858 kg (15,120 lbs) |
| Axle(s) & Suspension: | 10K: (2) 6,000 lb Axles 14K: (2) 7,000 lb Axles w/Easy Lube Spindles, Torsion Suspension |
| Tires: | 10K: ST225/75R15 LRE Radial 14K: ST235/80R16 LRE Radial |
| Brakes: | Electric on Both Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | 12,000 lbs Drop Leg Jack (2) 7,000 lbs Rear Stabilizing Jacks |
| Fenders: | HD Fenders |
| Deck Height: | 15" |
| Ramps: | 5' Spring Assisted Up-right Ramps |
| Floor: | Checker Plate Steel |
| Tongue Length: | 6' Models: 44" 7' Models: 52" |
| Tie Downs: | Stake Pockets & Rub Rails (8) D-Rings (3) Recessed Tie Downs on 6x12, 7x14 & 7x16 Models |
| Spare Tire Mount: | Passenger Side - Removeable |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|-----------|------------|----------------------|
| SL610-10K | 72" x 120" | 981 kg (2,163 lbs) |
| SL612-10K | 72" x 144" | 1,058 kg (2,332 lbs) |
| SL612-14K | 72" x 144" | 1,128 kg (2,487 lbs) |
| SL714-14K | 80" x 168" | 1,240 kg (2,734 lbs) |
| SL716-14K | 80" x 193" | 1,352 kg (2,981 lbs) |

Popular Options

| | |
|------------------------|--------------------|
| Spare Tire | Additional D-Rings |
| Lockable Steel Toolbox | Aluminum Wheels |
| Hydraulic Brakes | Heavy Floor |
| Galvanize Trailer | |

Dealer Information & Pricing





CANADA TRAILERS

Single Axle Gravity Tilt Trailers



Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 5K: 2,360 kg (5,200 lbs) 7K: 3,175 kg (7,000 lbs) |
| Axle(s) & Suspension: | 5K: (1) 6,000 lbs Axle 7K: (1) 7,000 lbs Axle w/Easy Lube Spindles, Torsion Suspension |
| Tires: | 5K: ST225/75R15 LRE Radial 7K: ST235/80R16 LRE Radial |
| Brakes: | Electric on Both Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | 7,000 lbs Drop Leg Jack |
| Deck Height: | 20" |
| Floor: | Pressure Treated Wood |
| Tongue Length: | 50" |
| Tie Downs: | Stake Pockets & (4) D-Rings |
| Spare Tire Mount: | Passenger Side- Removeable |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|----------|------------|--------------------|
| TL612-5K | 72" x 144" | 611 kg (1,346 lbs) |
| TL612-7K | 72" x 144" | 646 kg (1,424 lbs) |
| TL614-5K | 72" x 168" | 714 kg (1,575 lbs) |
| TL614-7K | 72" x 168" | 746 kg (1,644 lbs) |
| TL712-5K | 80" x 144" | 631 kg (1,392 lbs) |
| TL712-7K | 80" x 144" | 679 kg (1,496 lbs) |
| TL714-7K | 80" x 168" | 746 kg (1,644 lbs) |

Popular Options

| | |
|------------------------|--------------------|
| Spare Tire | Additional D-Rings |
| Lockable Steel Toolbox | Aluminum Wheels |
| Hydraulic Brakes | Heavy Floor |
| Galvanize Trailer | |

Dealer Information & Pricing





CANADA TRAILERS

Gravity Tilt Trailers w/4ft Stationary Deck



Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 6,858 kg (15,120 lbs) |
| Axle(s) & Suspension: | (2) 7,000 lb Axles w/Easy Lube Spindles, Torsion Suspension |
| Tires: | ST235/80R16 LRE Radial |
| Brakes: | Electric on Both Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | 12,000 lbs Drop Leg Jack |
| Fenders: | HD Fenders |
| Deck Height: | 24" |
| Stationary Deck: | 4' |
| Tilt Features: | Gravity Tilt with Hydraulic Lock & Hydraulic Cushion Cylinder |
| Floor: | Pressure Treated Wood |
| Tongue Length: | 52" |
| Tie Downs: | Stake Pockets & Rub Rails |
| Spare Tire Mount: | Passenger Side - Removeable |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|-----------|--------------|----------------------|
| TL717-14K | 75.5" x 210" | 1,277 kg (2,815 lbs) |
| TL721-14K | 75.5" x 252" | 1,370 kg (3,020 lbs) |

Popular Options

| | |
|------------------------|-------------------|
| Spare Tire | Galvanize Trailer |
| Lockable Steel Toolbox | Aluminum Wheels |
| Hydraulic Brakes | Gooseneck |
| D-Rings | |

Dealer Information & Pricing





CANADA TRAILERS

Electric Hydraulic Full Deck Tilt Trailers



Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 10K: 4,899 kg (10,800 lbs) 14K: 6,350 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs) |
| Axle(s) & Suspension: | 10K: (2) 6,000 lb Axles 14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| Tires: | 10K: ST225/75R15 LRE Radial 14K: ST235/80R16 LRE Radial 21KTR: ST235/80R16 LRE Radial |
| Brakes: | Electric on Both Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | 12,000 lbs Drop Leg Jack |
| Fenders: | HD Fenders |
| Deck Height: | 24" |
| Tilt Features: | Electric over Hydraulic Full Tilt 3" Hydraulic Cylinder Interstate Extreme Cycle Battery Lockable Steel Toolbox |
| Winch Plate: | Yes |
| Floor: | Pressure Treated Wood |
| Tongue Length: | 52" |
| Tie Downs: | Stake Pockets & Rub Rails |
| Spare Tire Mount: | Passenger Side- Removeable |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|--------------|------------|----------------------|
| ETL718-10K | 80" x 216" | 1,090 kg (2,403 lbs) |
| ETL720-10K | 80" x 240" | 1,150 kg (2,536 lbs) |
| ETL718-14K | 80" x 216" | 1,230 kg (2,711 lbs) |
| ETL720-14K | 80" x 240" | 1,293 kg (2,850 lbs) |
| ETL722-14K | 80" x 264" | 1,507 kg (3,322 lbs) |
| ETL724-14K | 80" x 288" | 1,637 kg (3,608 lbs) |
| ETL724-21KTR | 80" x 288" | 1,783 kg (3,930 lbs) |

Popular Options

| | |
|------------------|-------------------|
| Spare Tire | Torsion Axles |
| Hydraulic Brakes | Aluminum Wheels |
| D-Rings | Gooseneck |
| 16K (2) 8K Axles | Galvanize Trailer |

Dealer Information & Pricing





CANADA TRAILERS

Deck Over Hydraulic Power Tilt Trailers



Standard Features & Specifications

| | |
|----------------------------------|---|
| GVWR: | 14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs) |
| Axle(s) & Suspension: | 14K: (2) 7,000 lb Axles 21KTR: (3) 7000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| Tires: | ST235/80R16 LRE Radial |
| Brakes: | Electric on Both Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | 12,000 lb Drop Leg Jack |
| Deck Height: | 36" |
| Winch Plate: | Yes |
| Hoist Features: | Electric Over Hydraulic Full Deck Power Up/Power Down Tilt with Hand Remote. 5" Hydraulic Cylinder. Interstate Extreme Cycle Battery and Plug in Charger. Lockable Steel Toolbox. |
| Floor: | Pressure Treated Wood |
| Tongue Length: | 62" |
| Tie Downs: | Stake Pockets and Rub Rails |
| Spare Tire Mount: | Passenger Side of Box |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|----------------|-------------|----------------------|
| ETL822-14K | 102" x 264" | 2,004 kg (4,417 lbs) |
| ETL824-14K | 102" x 288" | 2,140 kg (4,717 lbs) |
| ETL826-14K | 102" x 312" | 2,276 kg (5,017 lbs) |
| ETL824-21KTR | 102" x 288" | 2,336 kg (5,150 lbs) |
| ETL826-21KTR | 102" x 312" | 2,513 kg (5,540 lbs) |
| GNETL822-14K | 102" x 264" | 2,344 kg (5,167 lbs) |
| GNETL824-14K | 102" x 288" | 2,434 kg (5,367 lbs) |
| GNETL826-14K | 102" x 312" | 2,548 kg (5,617 lbs) |
| GNETL824-21KTR | 102" x 288" | 6,226 kg (5,789 lbs) |
| GNETL826-21KTR | 102" x 312" | 2,785 kg (6,139 lbs) |

Popular Options

| | |
|-------------------------|---------------------|
| Spare Tire | D-Rings |
| Hydraulic Brakes | Sliding Winch Track |
| Galvanize Trailer | Aluminum Wheels |
| 16K: (2) 8,000 lb Axles | |

Dealer Information & Pricing





CANADA TRAILERS

Heavy Duty Dump Trailers



Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 7K: 3,429 kg (7,560 lbs) 10K: 4,899 kg (10,800 lbs) |
| Axle(s) & Suspension: | 7K: (2) 3,500 lb Axles 10K: (2) 6,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| Tires: | 7K: ST205/75R15 LRC Radial 10K: ST225/75R15 LRE Radial |
| Brakes: | Electric on Both Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | 7K Models: 7,000 lb Drop Leg Jack 10K Models: 12,000 lb Drop Leg Jack |
| Fenders: | HD Fenders |
| Deck Height: | 22" - 27" |
| Sides: | 20" Steel & 10" Wood Plank |
| Doors: | Barn Doors with Cam Lock |
| Load Cover: | Shielded Tarp and Roller |
| Hoist Features: | 3,000 psi Hydraulic Power Pack, 20' Hand Remote and Wireless Remote. 5" Hydraulic Cylinder & Scissor Hoist. Interstate Extreme Cycle Battery and Plug in Charger. Lockable Steel Toolbox. |
| Floor: | Steel |
| Tongue Length: | 52" |
| Tie Downs: | (4) Heavy Duty Welded In D-Rings |
| Spare Tire Mount: | Passenger Side of Box |

| | |
|-------------------------|--|
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|-------------|----------------|----------------------|
| DT510-7K | 60" x 118.5" | 1,232 kg (2,716 lbs) |
| DT610-7K | 71.5" x 118.5" | 1,310 kg (2,889 lbs) |
| DT510-10K | 60" x 118.5" | 1,346 kg (2,967 lbs) |
| DT610-10K | 71.5" x 118.5" | 1,413 kg (3,116 lbs) |
| DT612-10K | 71.5" x 142.5" | 1,534 kg (3,381 lbs) |
| DT6.512-10K | 77.5" x 142.5" | 1,625 kg (3,582 lbs) |

Popular Options

| | |
|------------------|--|
| Spare Tire | Additional D-Rings |
| Torsion Axles | Hydraulic Brakes |
| Aluminum Wheels | Two-Way Gate (Standard on DT6.512-10K) |
| Tarp Cover | Galvanize Trailer |
| Rear Stabilizers | 48" Sides |

Dealer Information & Pricing





CANADA TRAILERS

Ultra Duty Dump Trailers



Standard Features & Specifications

| | |
|----------------------------------|---|
| GVWR: | 14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs) |
| Axle(s) & Suspension: | 14K: (2) 7,000 lb Axles 21KTR: (3) 7000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| Tires: | ST235/80R16 LRE Radial |
| Brakes: | Electric on All Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | 12,000 lb Drop Leg Jack |
| Fenders: | HD Fenders |
| Deck Height: | 29" |
| Sides: | 20" steel + 10" Wood Plank |
| Doors: | Barn Doors with Cam Lock. Two Way Gate. |
| Load Cover: | Shielded Tarp & Roller |
| Hoist Features: | 3,000 psi Hydraulic Power Pack, 20' Hand Remote and Wireless Remote. 14K: 5" Hydraulic Cylinder 21KTR: 6" Hydraulic Cylinder, Both with Scissor Hoist. Interstate Extreme Cycle Battery and Plug in Charger. Lockable Steel Toolbox. |
| Floor: | Steel |
| Tongue Length: | 52" |
| Tie Downs: | 6' Models: (4), 83" Models: (6) Heavy Duty Welded In D-Rings |
| Spare Tire Mount: | Passenger Side of Box |

| | |
|-------------------------|---|
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |

Models

| | | |
|--------------|----------------|----------------------|
| DT612-14K | 71.5" x 142.5" | 1,669 kg (3,679 lbs) |
| DT6.512-14K | 77.5" x 142.5" | 1,743 kg (3,843 lbs) |
| DT8312-14K | 83" x 142.5" | 1,779 kg (3,923 lbs) |
| DT8314-14K | 83" x 166.5" | 1,934 kg (4,263 lbs) |
| DT8316-14K | 83" x 190.5" | 2,423 kg (5,341 lbs) |
| DT8314-21KTR | 83" x 166.5" | 2,342 kg (5,163 lbs) |
| DT8316-21KTR | 83" x 190.5" | 2,629 kg (5,796 lbs) |
| DT814-14K | 94" x 166.5" | 2,402 kg (5,295 lbs) |
| DT816-14K | 94" x 190.5" | 2,742 kg (6,044 lbs) |
| DT816-21KTR | 94" x 190.5" | 2,901 kg (6,396 lbs) |

Popular Options

| | |
|--------------------|-------------------|
| Spare Tire | Electric Brakes |
| Additional D-Rings | Aluminum Wheels |
| 5K Axle | Galvanize Trailer |
| Torsion Axle | |

Dealer Information & Pricing





CANADA TRAILERS

Gooseneck Dump Trailers



Standard Features & Specifications

| | |
|----------------------------------|---|
| GVWR: | 14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs) 24KD: 11,757 kg (25,920 lbs) |
| Axle(s) & Suspension: | 14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension 24KD: (2) 12,000 lb Axles w/Oil Bath Hubs, Slipper Spring Suspension |
| Tires: | ST235/80R16 LRE Radial |
| Brakes: | Electric on All Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | (2) 12,000 lb Drop Leg Jack |
| Fenders: | HD Fenders |
| Deck Height: | 7' Model: 29" 8' Model: 36" |
| Sides: | 20" steel + 10" Wood Plank |
| Doors: | Barn Doors with Cam Lock. Two Way Gate. |
| Load Cover: | Shielded Tarp & Roller |
| Hoist Features: | 3,000 psi Hydraulic Power Pack, 20' Hand Remote and Wireless Remote. 14K: 5" Hydraulic Cylinder 21KTR & 24KD: 6" Hydraulic Cylinder, Both with Scissor Hoist. Interstate Extreme Cycle Battery and Plug in Charger. Lockable Steel Toolbox. |
| Floor: | Steel |
| Tongue Length: | 52" |
| Tie Downs: | (6) Heavy Duty Welded In D-Rings |
| Spare Tire Mount: | Passenger Side of Box |

| | |
|-------------------------|--|
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|----------------|--------------|----------------------|
| GNDT8314-14K | 83" x 166.5" | 2,206 kg (4,863 lbs) |
| GNDT8316-14K | 83" x 190.5" | 2,695 kg (5,941 lbs) |
| GNDT8314-21KTR | 83" x 166.5" | 2,625 kg (5,788 lbs) |
| GNDT8316-21KTR | 83" x 190.5" | 2,901 kg (6,396 lbs) |
| GNDT814-21KTR | 94" x 166.5" | 2,656 kg (5,856 lbs) |
| GNDT816-21KTR | 94" x 190.5" | 2,719 kg (5,994 lbs) |
| GNDT814-24KD | 94" x 166.5" | 3,192 kg (7,038 lbs) |
| GNDT816-24KD | 94" x 190.5" | 3,484 kg (7,682 lbs) |

Popular Options

| | |
|--|---|
| Spare Tire | Additional D-Rings |
| Tarp Cover | Heavy Gauge Floor |
| Hydraulic Brakes | 6' Ramps |
| 48" High Sides | Galvanize Trailer |
| Rear Stabilizers | Aluminum Wheels, N/A on 16K & 24KD Models |
| 16K: (2) 8,000 lb Axles – N/A on 83" Models | |

Dealer Information & Pricing





CANADA TRAILERS

Straight Deck Pintle Series Trailers



Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 7K: 3,429 kg (7,560 lbs) 10K: 4,899 kg (10,800 lbs) 14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs) |
| Axle(s) & Suspension: | 7K: (2) 3,500 lb Axles 10K: (2) 6,000 lb Axles 14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles, w/Easy Lube Spindles, Slipper Spring Suspension |
| Tires: | 7K: ST205/75R15 LRC Radial 10K: ST225/75R15 LRE Radial 14K & 21KTR: ST235/80R16 LRE Radial |
| Brakes: | Electric on All Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | 12,000 lbs Drop Leg Jack |
| Ramps: | 7' Ramps, Stowed Under Deck |
| Deck Height: | 7K & 10K: 32" 14K – 24KD: 36" |
| Frame: | Light Weight, Rigid Frame Crossmembers every 16" |
| Side Steps: | On Both Sides |
| Floor: | Pressure Treated Wood |
| Tongue Length: | 62" |
| Tie Downs: | Stake Pockets & Rub Rails |
| Spare Tire Mount: | Optional – Tongue Mount Only |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|------------|-------------|----------------------|
| SD16-7K | 102" x 192" | 1,295 kg (2,885 lbs) |
| SD18-7K | 102" x 216" | 1,368 kg (3,015 lbs) |
| SD20-7K | 102" x 240" | 1,455 kg (3,208 lbs) |
| SD16-10K | 102" x 192" | 1,405 kg (3,098 lbs) |
| SD18-10K | 102" x 216" | 1,483 kg (3,269 lbs) |
| SD20-10K | 102" x 240" | 1,575 kg (3,473 lbs) |
| SD16-14K | 102" x 192" | 1,476 kg (3,254 lbs) |
| SD18-14K | 102" x 216" | 1,554 kg (3,425 lbs) |
| SD20-14K | 102" x 240" | 1,646 kg (3,629 lbs) |
| SD24-14K | 102" x 288" | 1,867 kg (4,117 lbs) |
| SD20-21KTR | 102" x 240" | 1,994 kg (4,395 lbs) |
| SD24-21KTR | 102" x 288" | 2,177 kg (4,799 lbs) |
| SD28-21KTR | 102" x 336" | 2,636 kg (5,209 lbs) |
| SD30-21KTR | 102" x 360" | 2,496 kg (5,502 lbs) |

Popular Options

| | |
|----------------------|---------------------------------|
| Spare Tire | Dual 12K Jacks |
| Winch Track | Hydraulic Brakes |
| Sliding Winch & Stap | D-Rings |
| Galvanize Trailer | Torsion Axles, Not |
| 16K – Two 8K Axles | Available on 24KD & 30KD |
| 24KD – Two 12K Axles | Aluminum Wheels, Not |
| 30KD – Two 15K Axles | Available on 16K, 24KD and 30KD |

Dealer Information & Pricing





Straight Deck Gooseneck Series Trailers



Standard Features & Specifications

| | |
|----------------------------------|---|
| GVWR: | 14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs) 24KD: 10,890 kg (25,920 lbs) |
| Axle(s) & Suspension: | 14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension 24KD: (2) 12,000 lb Axle, Dually w/Oil Bath Hubs, Slipper Spring Suspension |
| Tires: | ST235/80R16 LRE Radial |
| Brakes: | Electric on All Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | (2) 12,000 lb Drop Leg Jacks |
| Ramps: | 7' Ramps, Stowed Under Deck |
| Deck Height: | 36" |
| Frame: | Light Weight, Rigid Frame Crossmembers every 16" |
| Floor: | Pressure Treated Wood |
| Side Steps: | On Both Sides |
| Gooseneck Length: | 9' |
| Tie Downs: | Stake Pockets & Rub Rails |
| Spare Tire Mount: | On Gooseneck |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|--------------|-------------|----------------------|
| GNSD16-14K | 102" x 192" | 1,758 kg (3,875 lbs) |
| GNSD18-14K | 102" x 216" | 1,838 kg (4,051 lbs) |
| GNSD20-14K | 102" x 240" | 1,995 kg (4,398 lbs) |
| GNSD24-14K | 102" x 288" | 2,205 kg (4,861 lbs) |
| GNSD18-21KTR | 102" x 216" | 2,100 kg (4,629 lbs) |
| GNSD20-21KTR | 102" x 240" | 2,220 kg (4,849 lbs) |
| GNSD24-21KTR | 102" x 288" | 2,432 kg (5,362 lbs) |
| GNSD28-21KTR | 102" x 336" | 2,621 kg (5,779 lbs) |
| GNSD30-21KTR | 102" x 360" | 2,698 kg (5,947 lbs) |
| GNSD20-24KD | 102" x 240" | 2,477 kg (5,461 lbs) |
| GNSD24-24KD | 102" x 288" | 2,693 kg (5,938 lbs) |
| GNSD28-24KD | 102" x 336" | 2,884 kg (6,358 lbs) |
| GNSD30-24KD | 102" x 360" | 3,001 kg (6,615 lbs) |

Popular Options

| | |
|------------------------|--------------------------------------|
| Spare Tire | Torsion Axles, Not Available on 24KD |
| Winch Track | Hydraulic Brakes |
| Sliding Winch & Stap | D-Rings |
| Lockable Steel Toolbox | Aluminum Wheels |
| King Pin | Galvanize Trailer |
| 16K – Two 8K Axles | |
| 30KD-Two 15K Axles | |

Dealer Information & Pricing





CANADA TRAILERS

Beavertail Deck Over Pintle Series Trailers



Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 14K: 6,858 kg (15,120 lbs) |
| Axle(s) & Suspension: | 14K: (2) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| Tires: | ST235/80R16 LRE Radial |
| Brakes: | Electric on All Axles |
| Coupler: | Adjustable 2-5/16" Coupler or 3" Lunette Eye |
| Jack: | 12,000 lbs Drop Leg Jack |
| Beavertail: | 5' Beavertail with Wood Floor |
| Ramps: | 5' Spring Assisted Wedge Ramps |
| Deck Height: | 36" |
| Frame: | Light Weight, Rigid Frame Crossmembers every 16" |
| Floor: | Pressure Treated Wood |
| Tongue Length: | 62" |
| Tie Downs: | Stake Pockets & Rub Rails |
| Side Steps: | On Both Sides |
| Spare Tire Mount: | Optional – Tongue Mount Only |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|----------|-------------|----------------------|
| BT22-14K | 102" x 264" | 1,894 kg (4,175 lbs) |
| BT25-14K | 102" x 300" | 2,020 kg (4,453 lbs) |

Popular Options

| | |
|------------------------|------------------|
| Spare Tire | Hydraulic Brakes |
| Lockable Steel Toolbox | D-Rings |
| Galvanize Trailer | Aluminum Wheels |
| Full Width Ramps | Dual 12K Jacks |
| 16K – Two 8K Axles | |

Dealer Information & Pricing





CANADA TRAILERS

Premium Pintle Series Trailers



Standard Features & Specifications

| | |
|----------------------------------|---|
| GVWR: | 14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs) 24KD: 11,757 kg (25,920 lbs) |
| Axle(s) & Suspension: | 14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension 24KD: (2) 12,000 lb Axle, Dually w/Oil Bath Hubs, Slipper Spring Suspension |
| Tires: | ST235/80R16 LRE Radial |
| Brakes: | Electric on All Axles |
| Coupler: | Adjustable 3" Lunette Eye |
| Jack: | 12,000 lb Drop Leg Jack |
| Ramps: | Full Width Ramps |
| Deck Height: | 36" |
| Frame: | 12" @ 22 lbs. Heavy Wide-Flange Beams. Crossmembers every 16". |
| Floor: | Pressure Treated Wood |
| Tongue Length: | 62" |
| Beavertail: | 5' Angle Iron Beavertail |
| Tie Downs: | Stake Pockets & Rub Rails |
| Side Steps: | On Both Sides |
| Winch Track: | Driver's Side |
| Spare Tire Mount: | Optional – Tongue Mount Only |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|--------------|-------------|----------------------|
| PHFT22-14K | 102" x 264" | 2,775 kg (5,015 lbs) |
| PHFT25-14K | 102" x 300" | 2,555 kg (5,632 lbs) |
| PHFT28-14K | 102" x 336" | 2,737 kg (6,035 lbs) |
| PHFT30-14K | 102" x 360" | 2,882 kg (6,354 lbs) |
| PHFT25-21KTR | 102" x 300" | 2,757 kg (6,078 lbs) |
| PHFT28-21KTR | 102" x 336" | 2,940 kg (6,481 lbs) |
| PHFT30-21KTR | 102" x 360" | 3,084 kg (6,800 lbs) |
| PHFT32-21KTR | 102" x 384" | 3,192 kg (7,038 lbs) |
| PHFT25-24KD | 102" x 300" | 3,020 kg (6,657 lbs) |
| PHFT28-24KD | 102" x 336" | 3,201 kg (7,057 lbs) |
| PHFT30-24KD | 102" x 360" | 3,348 kg (7,381 lbs) |
| PHFT32-24KD | 102" x 384" | 3,455 kg (7,618 lbs) |

Popular Options

| | |
|--------------------------------------|---|
| Torsion Axles, Not Available on 24KD | Aluminum Wheels – Not Available on 24KD |
| Spare Tire | D-Rings |
| 6' Tongue | Hydraulic Brakes |
| Dual 12K lb Jacks | 16K – Two 8K Axles |
| Lockable Steel Toolbox | 30KD-Two 15K Axles |
| Galvanize Trailer | |

Dealer Information & Pricing





CANADA TRAILERS

Premium Gooseneck Series Trailers



Standard Features & Specifications

| | |
|----------------------------------|--|
| GVWR: | 14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs) 24KD: 11,757 kg (25,920 lbs) |
| Axle(s) & Suspension: | 14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension. 24KD: (2) 12,000 lb Axle, Dually w/Oil Bath Hubs, Slipper Spring Suspension |
| Tires: | ST235/80R16 LRE Radial |
| Brakes: | Electric on All Axles |
| Coupler: | Adjustable Gooseneck Coupler |
| Jack: | (2) 12,000 lb Drop Leg Jack |
| Ramps: | 5' Full Width Ramps |
| Deck Height: | 36" |
| Frame: | 12" @ 22 lbs. Heavy Wide-Flange Beams. Crossmembers every 16". |
| Floor: | Pressure Treated Wood |
| Gooseneck Length: | 9' |
| Beavertail: | 5' Angle Iron Beavertail |
| Tie Downs: | Stake Pockets & Rub Rails |
| Side Steps: | On Both Sides |
| Winch Track: | Driver's Side |
| Spare Tire Mount: | On Gooseneck |
| Lights: | Transport Canada & DOT Approved, Sealed Beam LED |
| Electrical/Plug: | Sealed Harness & 7 Way RV Plug |
| Finish: | Powder Coat & Scorpion Stone Guard |


Models

| | | |
|--------------|-------------|----------------------|
| GNFT25-14K | 102" x 300" | 2,780 kg (6,129 lbs) |
| GNFT28-14k | 102" x 336" | 2,940 kg (6,481 lbs) |
| GNFT30-14K | 102" x 360" | 3,084 kg (6,800 lbs) |
| GNFT32-14K | 102" x 384" | 3,187 kg (7,027 lbs) |
| GNFT25-21KTR | 102" x 300" | 2,976 kg (6,562 lbs) |
| GNFT28-21KTR | 102" x 336" | 3,136 kg (6,914 lbs) |
| GNFT30-21KTR | 102" x 360" | 3,281 kg (7,233 lbs) |
| GNFT32-21KTR | 102" x 384" | 3,384 kg (7,460 lbs) |
| GNFT25-24KD | 102" x 300" | 3,240 kg (7,143 lbs) |
| GNFT28-24KD | 102" x 336" | 3,397 kg (7,489 lbs) |
| GNFT30-24KD | 102" x 360" | 3,543 kg (7,812 lbs) |
| GNFT32-24KD | 102" x 384" | 3,647 kg (8,040 lbs) |

Popular Options

| | |
|--|--------------------------------------|
| Aluminum Wheels, Not Available on 16K & 24KD | Torsion Axles, Not Available on 24KD |
| King Pin | Hydraulic Brakes |
| Spare Tire | D-Rings |
| 16K – Two 8K Axles | Galvanize Trailer |
| 30KD-Two 15K Axles | |

Dealer Information & Pricing





CANADA TRAILERS

Canada Trailers Manufacturing Limited

11918 Imperial Road, Hwy. 73
Aylmer Ontario
N5H 2R3

Phone: 519-765-1717

Fax: 519-765-1725

www.canadatrailers.com