



# CANADA TRAILERS

---



---

## Canada Trailers Manufacturing Limited

11918 Imperial Road, Hwy. 73  
Aylmer Ontario  
N5H 2R3

Phone: 519-765-1717

Fax: 519-765-1725

[www.canadatrailers.com](http://www.canadatrailers.com)





## Table of Contents

| Trailer Model                                          | Page # |
|--------------------------------------------------------|--------|
| Single Axle Steel Side Utility Trailers                | 1      |
| Tandem Axle Steel Side Landscape/Utility Trailers      | 2      |
| H.D. Tandem Axle Steel Side Landscape/Utility Trailers | 3      |
| Car Trailers                                           | 4      |
| Equipment Trailers                                     | 5      |
| Gooseneck Equipment Trailers                           | 6      |
| 102" Wide Equipment Trailers w/ 4' Max Ramps           | 7      |
| 102" Wide Gooseneck Equipment Trailers w/ 4' Max Ramps | 8      |
| Low Incline Scissor Lift Trailers                      | 9      |
| Single Axle Gravity Tilt Trailers                      | 10     |
| Gravity Tilt Trailers w/ 4' Stationary Deck            | 11     |
| Electric Hydraulic Full Deck Tilt Trailers             | 12     |
| Deck Over Hydraulic Power Tilt Trailers                | 13     |
| 102" Wide Hydraulic Full Deck Tilt Trailers            | 14     |
| 102" Wide Gooseneck Hyd. Full Deck Tilt Trailers       | 15     |
| Heavy Duty Dump Trailers                               | 16     |
| Ultra Duty Dump Trailers                               | 17     |
| Ultra Duty Deck Over Dump Trailers                     | 18     |
| Gooseneck Dump Trailers                                | 19     |
| Straight Deck Pintle Series Trailers                   | 20     |
| Straight Deck Gooseneck Series Trailers                | 21     |
| Beavertail Deck Over Pintle Series Trailers            | 22     |
| Premium Pintle Series Trailers                         | 23     |
| Premium Gooseneck Series Trailers                      | 24     |
| Gooseneck XD Series Trailers                           | 25     |



## Single Axle Steel Side Utility Trailers



### Standard Features & Specifications

|                                  |                                                                                                                  |
|----------------------------------|------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 3K: 1,356 kg (2,990 lbs)<br>3.5K: 1,587 kg (3,500 lbs)<br>5K: 2,267 kg (5,000 lbs)                               |
| <b>Axle(s) &amp; Suspension:</b> | 3K & 3.5K: (1) 3,500 lb Axle w/Easy Lube Spindles, Double Eye Spring Suspension<br>5K: (1) 5,200 lb Axle w/ same |
| <b>Tires:</b>                    | 3K & 3.5K: ST205/75R15 LRC Radial<br>5K: ST225/75R15 LRE Radial                                                  |
| <b>Brakes:</b>                   | Electric                                                                                                         |
| <b>Coupler:</b>                  | 2" A-Frame Coupler                                                                                               |
| <b>Jack:</b>                     | 3 & 3.5K: 2,000 lbs A-Frame Jack<br>5K: 5,000 lbs A-Frame Jack                                                   |
| <b>Deck Height:</b>              | 17"                                                                                                              |
| <b>Sides:</b>                    | 15" Solid Steel + 3" Tie Rail                                                                                    |
| <b>Ramp:</b>                     | 3 & 3.5K: 4' Straight Ramp w/ Mesh<br>5K: Spring Assisted Ramps                                                  |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                                            |
| <b>Tongue Length:</b>            | 5' Models : 42"<br>6' Models : 46"<br>7' Models : 48"                                                            |
| <b>Tie Downs:</b>                | (4) Welded In D-Rings                                                                                            |
| <b>Spare Tire Mount:</b>         | Front of Bed, Upright                                                                                            |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                                                 |
| <b>Electrical/Plug:</b>          | 3K: Sealed Harness & 4 Way Flat Plug<br>3.5K & 5K: 7 Way RV Plug                                                 |
| <b>Finish:</b>                   | Powder Coat – Matte Black                                                                                        |


### Models

|            |              |                    |
|------------|--------------|--------------------|
| UT58-3K    | 60.5" x 98"  | 423 kg (930 lbs)   |
| UT510-3K   | 60.5" x 122" | 472 kg (1,038 lbs) |
| UT512-3K   | 60.5" x 146" | 518 kg (1,141 lbs) |
| UT514-3K   | 60.5" x 170" | 556 kg (1,224 lbs) |
| UT610-3K   | 72" x 122"   | 567 kg (1,248 lbs) |
| UT612-3K   | 72" x 146"   | 605 kg (1,332 lbs) |
| UT712-3.5K | 82" x 146"   | 666 kg (1,466 lbs) |
| UT714-3.5K | 82" x 170"   | 714 kg (1,571 lbs) |
| UT712-5K   | 82" x 146"   | 752 kg (1,654 lbs) |
| UT714-5K   | 82" x 170"   | 858 kg (1,888 lbs) |

### Popular Options

|                              |                   |
|------------------------------|-------------------|
| Bifold Ramp (5ft & 6ft only) | Galvanize Trailer |
| Additional D-Rings           | Aluminum Wheels   |
| 5K Axle                      |                   |

### Dealer Information & Pricing





## Tandem Axle Steel Side Landscape/Utility Trailers



### Standard Features & Specifications

|                                  |                                                                    |
|----------------------------------|--------------------------------------------------------------------|
| <b>GVWR:</b>                     | 3,429 kg (7,560 lbs)                                               |
| <b>Axle(s) &amp; Suspension:</b> | (2) 3,500 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| <b>Tires:</b>                    | ST205/75R15 LRC Radial                                             |
| <b>Brakes:</b>                   | Electric on Both Axles                                             |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                       |
| <b>Jack:</b>                     | 7,000 lbs A-Frame Jack                                             |
| <b>Fenders:</b>                  | HD Fenders                                                         |
| <b>Deck Height:</b>              | 19"                                                                |
| <b>Sides:</b>                    | 15" Solid Steel + 3" Tie Rail                                      |
| <b>Ramps:</b>                    | 4' Split Ramps w/ Mesh                                             |
| <b>Floor:</b>                    | Pressure Treated Wood                                              |
| <b>Tongue Length:</b>            | 53"                                                                |
| <b>Tie Downs:</b>                | Stake Pockets<br>Welded In D-Rings                                 |
| <b>Spare Tire Mount:</b>         | Front of Bed, Upright                                              |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                   |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                     |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                 |


### Models

|          |            |                      |
|----------|------------|----------------------|
| UT712-7K | 82" x 145" | 879 kg (1,934 lbs)   |
| UT714-7K | 82" x 169" | 898 kg (1,976 lbs)   |
| UT716-7K | 82" x 193" | 982 kg (2,160 lbs)   |
| UT718-7K | 82" x 217" | 1,012 kg (2,226 lbs) |
| UT720-7K | 82" x 241" | 1,070 kg (2,354 lbs) |

### Popular Options

|                        |                    |
|------------------------|--------------------|
| Spare Tire             | Torsion Axles      |
| Lockable Steel Toolbox | Additional D-Rings |
| 7000 lbs Drop Leg Jack | Aluminum Wheels    |
| Rear Stabilizers       | Galvanize Trailer  |
| Side ATV Ramps         |                    |

### Dealer Information & Pricing





## H.D. Tandem Axle Steel Side Landscape/Utility Trailers



### Standard Features & Specifications

|                                  |                                                                                                    |
|----------------------------------|----------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 10K: 4,899 kg (10,800 lbs)<br>14K: 6,858 kg (15,120 lbs)                                           |
| <b>Axle(s) &amp; Suspension:</b> | 10K: (2) 6,000 lb Axles<br>14K: (2) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| <b>Tires:</b>                    | 10K: ST225/75R15 LRE Radial<br>14K: ST235/80R16 LRE Radial                                         |
| <b>Brakes:</b>                   | Electric on Both Axles                                                                             |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                                                       |
| <b>Jack:</b>                     | 12,000 lbs Drop Leg Jack                                                                           |
| <b>Fenders:</b>                  | HD Fenders                                                                                         |
| <b>Deck Height:</b>              | 20"                                                                                                |
| <b>Sides:</b>                    | 15" Solid Steel + 3" Tie Rail                                                                      |
| <b>Ramps:</b>                    | 5' Heavy Duty Spring Assisted Split Ramps w/ Mesh                                                  |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                              |
| <b>Tongue Length:</b>            | 53"                                                                                                |
| <b>Tie Downs:</b>                | Stake Pockets<br>Welded In D-Rings                                                                 |
| <b>Spare Tire Mount:</b>         | Front of Bed, Upright                                                                              |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                                   |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                                     |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                                 |


### Models

|           |            |                      |
|-----------|------------|----------------------|
| UT716-10K | 82" x 193" | 1,201 kg (2,642 lbs) |
| UT718-10K | 82" x 217" | 1,245 kg (2,738 lbs) |
| UT720-10K | 82" x 241" | 1,378 kg (3,032 lbs) |
| UT722-10K | 82" x 265" | 1,442 kg (3,174 lbs) |
| UT724-10K | 82" x 288" | 1,511 kg (3,326 lbs) |
| UT716-14K | 82" x 193" | 1,355 kg (2,982 lbs) |
| UT718-14K | 82" x 217" | 1,420 kg (3,124 lbs) |
| UT720-14K | 82" x 241" | 1,508 kg (3,318 lbs) |
| UT722-14K | 82" x 265" | 1,615 kg (3,553 lbs) |
| UT724-14K | 82" x 288" | 1,688 kg (3,714 lbs) |

### Popular Options

|                        |                    |
|------------------------|--------------------|
| Spare Tire             | Torsion Axles      |
| Lockable Steel Toolbox | Additional D-Rings |
| Hydraulic Brakes       | Aluminum Wheels    |
| Rear Stabilizers       | Galvanize Trailer  |

### Dealer Information & Pricing





### Standard Features & Specifications

|                                  |                                                                    |
|----------------------------------|--------------------------------------------------------------------|
| <b>GVWR:</b>                     | 3,429 kg (7,560 lbs)                                               |
| <b>Axle(s) &amp; Suspension:</b> | (2) 3,500 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| <b>Tires:</b>                    | ST205/75R15 LRC Radial                                             |
| <b>Brakes:</b>                   | Electric on Both Axles                                             |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                       |
| <b>Jack:</b>                     | 7,000 lbs A-Frame Jack                                             |
| <b>Fenders:</b>                  | HD Fenders                                                         |
| <b>Deck Height:</b>              | 23"                                                                |
| <b>Sides:</b>                    | 2' with Wood Floor                                                 |
| <b>Ramps:</b>                    | 4' Ramps – Stored Under Deck                                       |
| <b>Floor:</b>                    | Pressure Treated Wood                                              |
| <b>Tongue Length:</b>            | 53"                                                                |
| <b>Tie Downs:</b>                | Stake Pockets                                                      |
| <b>Spare Tire Mount:</b>         | Passenger Side- Removeable                                         |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                   |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                     |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                 |


### Models

|          |            |                      |
|----------|------------|----------------------|
| CE714-7K | 82" x 168" | 951 kg (2,092 lbs)   |
| CE716-7K | 82" x 192" | 982 kg (2,160 lbs)   |
| CE718-7K | 82" x 216" | 1,013 kg (2,228 lbs) |
| CE720-7K | 82" x 240" | 1,083 kg (2,382 lbs) |

### Popular Options

|                                   |                   |
|-----------------------------------|-------------------|
| Spare Tire                        | Torsion Axles     |
| Lockable Steel Toolbox            | Straight Deck     |
| 7000 lbs Drop Leg Jack            | Aluminum Wheels   |
| 4' Beaver Tail                    | Galvanize Trailer |
| 5' Spring Assisted Up-right Ramps | Hydraulic Brakes  |

### Dealer Information & Pricing





### Standard Features & Specifications

|                                  |                                                                                                                                    |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 10K: 4,899 kg (10,800 lbs)<br>14K: 6,858 kg (15,120 lbs)<br>21KTR: 10,287 kg (22,680 lbs)                                          |
| <b>Axle(s) &amp; Suspension:</b> | 10K: (2) 5,200 lb Axles<br>14K: (2) 7,000 lb Axles<br>21KTR: (3) 7,000 lb Axles<br>w/Easy Lube Spindles, Slipper Spring Suspension |
| <b>Tires:</b>                    | 10K: ST225/75R15 LRE Radial<br>14K & 21KTR: ST235/80R16 LRE Radial                                                                 |
| <b>Brakes:</b>                   | Electric on all Axles                                                                                                              |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or<br>3" Lunette Eye                                                                                    |
| <b>Jack:</b>                     | 12,000 lbs Drop Leg Jack                                                                                                           |
| <b>Fenders:</b>                  | HD Fenders                                                                                                                         |
| <b>Deck Height:</b>              | 24"                                                                                                                                |
| <b>Beavertail:</b>               | 2' with Wood Floor                                                                                                                 |
| <b>Ramps:</b>                    | 5' Spring Assisted Up-right Ramps                                                                                                  |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                                                              |
| <b>Tongue Length:</b>            | 52"                                                                                                                                |
| <b>Tie Downs:</b>                | Stake Pockets & Rub Rails                                                                                                          |
| <b>Spare Tire Mount:</b>         | Passenger Side- Removeable                                                                                                         |
| <b>Lights:</b>                   | Transport Canada & DOT Approved,<br>Sealed Beam LED                                                                                |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                                                                     |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                                                                 |

### Models

|             |            |                      |
|-------------|------------|----------------------|
| CE714-10K   | 83" x 168" | 1,092 kg (2,403 lbs) |
| CE716-10K   | 83" x 192" | 1,173 kg (2,580 lbs) |
| CE718-10K   | 83" x 216" | 1,251 kg (2,752 lbs) |
| CE720-10K   | 83" x 240" | 1,339 kg (2,946 lbs) |
| CE714-14K   | 83" x 168" | 1,163 kg (2,559 lbs) |
| CE716-14K   | 83" x 192" | 1,224 kg (2,692 lbs) |
| CE718-14K   | 83" x 216" | 1,303 kg (2,867 lbs) |
| CE720-14K   | 83" x 240" | 1,348 kg (2,966 lbs) |
| CE722-14K   | 83" x 264" | 1,457 kg (3,205 lbs) |
| CE724-14K   | 83" x 288" | 1,523 kg (3,350 lbs) |
| CE720-21KTR | 83" x 240" | 1,795 kg (3,950 lbs) |
| CE722-21KTR | 83" x 264" | 1,831 kg (4,028 lbs) |
| CE724-21KTR | 83" x 288" | 1,873 kg (4,120 lbs) |

### Popular Options

|                                            |                   |
|--------------------------------------------|-------------------|
| Spare Tire                                 | Torsion Axles     |
| Lockable Steel Toolbox                     | 8K Axles          |
| 5' Extra Wide Ramps                        | Aluminum Wheels   |
| Hydraulic Brakes                           | Galvanize Trailer |
| 102" Wide w/ Stand-up or<br>Pull-out Ramps | Straight Deck     |

### Dealer Information & Pricing







## Gooseneck Equipment Trailers



### Standard Features & Specifications

|                                  |                                                                                                         |
|----------------------------------|---------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 14K: 6,858 kg (15,120 lbs)<br>21KTR: 10,287 kg (22,680 lbs)                                             |
| <b>Axle(s) &amp; Suspension:</b> | 14K: (2) 7,000 lb Axles<br>21KTR: (3) 7,000 lb Axles<br>w/Easy Lube Spindles, Slipper Spring Suspension |
| <b>Tires:</b>                    | ST235/80R16 LRE Radial                                                                                  |
| <b>Brakes:</b>                   | Electric on all Axles                                                                                   |
| <b>Coupler:</b>                  | Adjustable Gooseneck Coupler                                                                            |
| <b>Jack:</b>                     | 12,000 lbs Drop Leg Jack                                                                                |
| <b>Fenders:</b>                  | HD Fenders                                                                                              |
| <b>Deck Height:</b>              | 24"                                                                                                     |
| <b>Beavertail:</b>               | 2' with Wood Floor                                                                                      |
| <b>Ramps:</b>                    | 5' Spring Assisted Up-right Ramps                                                                       |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                                   |
| <b>Gooseneck Length:</b>         | 9'                                                                                                      |
| <b>Tie Downs:</b>                | Stake Pockets & Rub Rails                                                                               |
| <b>Spare Tire Mount:</b>         | Passenger Side - Removeable                                                                             |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                                        |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                                          |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                                      |



### Models

|               |            |                      |
|---------------|------------|----------------------|
| GNCE720-14K   | 83" x 240" | 1,871 kg (4,116 lbs) |
| GNCE722-14K   | 83" x 264" | 1,970 kg (4,355 lbs) |
| GNCE724-14K   | 83" x 288" | 2,045 kg (4,500 lbs) |
| GNCE726-14K   | 83" x 312" | 2,117 kg (4,658 lbs) |
| GNCE728-14K   | 83" x 336" | 2,210 kg (4,861 lbs) |
| GNCE720-21KTR | 83" x 240" | 2,318 kg (5,100 lbs) |
| GNCE722-21KTR | 83" x 264" | 2,354 kg (5,178 lbs) |
| GNCE724-21KTR | 83" x 288" | 2,395 kg (5,270 lbs) |
| GNCE726-21KTR | 83" x 312" | 2,514 kg (5,530 lbs) |
| GNCE728-21KTR | 83" x 336" | 2,630 kg (5,785 lbs) |
| GNCE732-21KTR | 83" x 384" | 2,791 kg (6,140 lbs) |

### Popular Options

|                                         |                   |
|-----------------------------------------|-------------------|
| Spare Tire                              | Torsion Axles     |
| Lockable Steel Toolbox                  | 8K Axles          |
| 5' Extra Wide Ramps                     | Aluminum Wheels   |
| Winch Plate                             | Galvanize Trailer |
| Hydraulic Brakes                        | Straight Deck     |
| 102" Wide w/ Stand-up or Pull-out Ramps |                   |

### Dealer Information & Pricing





## 102" Equipment Trailers w/4' Max Ramps



### Standard Features & Specifications

|                                  |                                                                           |
|----------------------------------|---------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 14K: 6,858 kg (15,120 lbs)                                                |
|                                  | 16K: 7,855 kg (17,280 lbs)                                                |
|                                  | 21KTR: 10,287 kg (22,680 lbs)                                             |
| <b>Axle(s) &amp; Suspension:</b> | 14K: (2) 7,000 lb Axles                                                   |
|                                  | 16K: (2) 8,000 lb Axles                                                   |
|                                  | 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| <b>Tires:</b>                    | 14K: ST235/80R16 LRE Radial                                               |
|                                  | 16K: 215/75R17.5 LRH Radial                                               |
|                                  | 21KTR: ST235/80R16 LRE Radial                                             |
| <b>Brakes:</b>                   | Electric on all Axles                                                     |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                              |
| <b>Jack:</b>                     | 12,000 lbs Drop Leg Jack                                                  |
| <b>Fenders:</b>                  | HD Drive Over Fenders                                                     |
| <b>Deck Height:</b>              | 24"                                                                       |
| <b>Beavertail:</b>               | 4' with Wood Floor                                                        |
| <b>Ramps:</b>                    | 4' Spring Assisted Fold Flat Mega Ramps                                   |
| <b>Floor:</b>                    | Pressure Treated Wood                                                     |
| <b>Tongue Length:</b>            | 52"                                                                       |
| <b>Tie Downs:</b>                | Stake Pockets, Rub Rails & D-Rings                                        |
| <b>Spare Tire Mount:</b>         | Passenger Side - Removeable                                               |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                          |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                            |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                        |


### Models

|                |             |                      |
|----------------|-------------|----------------------|
| CE102x22-14K   | 102" x 264" | 1,713 kg (3,769 lbs) |
| CE102x24-14K   | 102" x 288" | 1,805 kg (3,971 lbs) |
| CE102x26-14K   | 102" x 312" | 1,905 kg (4,191 lbs) |
| CE102x22-16K   | 102" x 264" | 1,871 kg (4,116 lbs) |
| CE102x24-16K   | 102" x 288" | 1,974 kg (4,342 lbs) |
| CE102x26-16K   | 102" x 312" | 2,089 kg (4,595 lbs) |
| CE102x26-21KTR | 102" x 312" | 2,215 kg (4,873 lbs) |
| CE102x28-21KTR | 102" x 336" | 2,422 kg (5,329 lbs) |
| CE102x32-21KTR | 102" x 384" | 2,564 kg (5,640 lbs) |

### Popular Options

|                        |                    |
|------------------------|--------------------|
| Spare Tire             | Galvanize Trailer  |
| Lockable Steel Toolbox | Aluminum Wheels    |
| Hydraulic Brakes       | Straight Deck      |
| Gooseneck              | Additional D-Rings |

### Dealer Information & Pricing





## 102" Gooseneck Equip. Trailers w/4' Max Ramps



### Standard Features & Specifications

|                                  |                                                                                                                                 |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 14K: 6,858 kg (15,120 lbs)<br>16K: 7,855 kg (17,280 lbs)<br>21KTR: 10,287 kg (22,680 lbs)                                       |
| <b>Axle(s) &amp; Suspension:</b> | 14K: (2) 7,000 lb Axles<br>16K: (2) 8,000 lb Axles<br>21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension |
| <b>Tires:</b>                    | 14K: ST235/80R16 LRE Radial<br>16K: 215/75R17.5 LRH Radial<br>21KTR: ST235/80R16 LRE Radial                                     |
| <b>Brakes:</b>                   | Electric on all Axles                                                                                                           |
| <b>Coupler:</b>                  | Adjustable Gooseneck Coupler                                                                                                    |
| <b>Jack:</b>                     | 12,000 lbs Drop Leg Jacks                                                                                                       |
| <b>Fenders:</b>                  | HD Drive Over Fenders                                                                                                           |
| <b>Deck Height:</b>              | 24"                                                                                                                             |
| <b>Beavertail:</b>               | 4' with Wood Floor                                                                                                              |
| <b>Ramps:</b>                    | 4' Spring Assisted Fold Flat Mega Ramps                                                                                         |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                                                           |
| <b>Winch Plate:</b>              | Yes, Raised Between Gooseneck                                                                                                   |
| <b>Gooseneck Length:</b>         | 9'                                                                                                                              |
| <b>Tie Downs:</b>                | Stake Pockets, Rub Rails & D-Rings                                                                                              |
| <b>Spare Tire Mount:</b>         | Passenger Side- Removeable                                                                                                      |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                                                                |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                                                                  |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                                                              |

### Models

|                  |             |                      |
|------------------|-------------|----------------------|
| GNCE102x22-14K   | 102" x 264" | 2,225 kg (4,895 lbs) |
| GNCE102x24-14K   | 102" x 288" | 2,308 kg (5,078 lbs) |
| GNCE102x26-14K   | 102" x 312" | 2,434 kg (5,354 lbs) |
| GNCE102x22-16K   | 102" x 264" | 2,291 kg (5,040 lbs) |
| GNCE102x24-16K   | 102" x 288" | 2,420 kg (5,325 lbs) |
| GNCE102x26-16K   | 102" x 312" | 2,643 kg (5,815 lbs) |
| GNCE102x26-21KTR | 102" x 312" | 2,607 kg (5,736 lbs) |
| GNCE102x28-21KTR | 102" x 336" | 2,708 kg (5,958 lbs) |
| GNCE102x32-21KTR | 102" x 384" | 2,943 kg (6,475 lbs) |

### Popular Options

|                    |                   |
|--------------------|-------------------|
| Spare Tire         | Aluminum Wheels   |
| Additional D-Rings | Galvanize Trailer |
| Hydraulic Brakes   | Straight Deck     |

### Dealer Information & Pricing





## Low Incline Scissor Lift Trailers



### Standard Features & Specifications

|                                  |                                                                     |
|----------------------------------|---------------------------------------------------------------------|
| <b>GVWR:</b>                     | 10K: 4,899 kg (10,800 lbs)                                          |
|                                  | 14K: 6,858 kg (15,120 lbs)                                          |
| <b>Axle(s) &amp; Suspension:</b> | 10K: (2) 6,000 lb Axles                                             |
|                                  | 14K: (2) 7,000 lb Axles<br>w/Easy Lube Spindles, Torsion Suspension |
| <b>Tires:</b>                    | 10K: ST225/75R15 LRE Radial                                         |
|                                  | 14K: ST235/80R16 LRE Radial                                         |
| <b>Brakes:</b>                   | Electric on Both Axles                                              |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                        |
| <b>Jack:</b>                     | 12,000 lbs Drop Leg Jack<br>(2) 7,000 lbs Rear Stabilizing Jacks    |
| <b>Fenders:</b>                  | HD Fenders                                                          |
| <b>Deck Height:</b>              | 15"                                                                 |
| <b>Ramps:</b>                    | 5' Spring Assisted Up-right Ramps                                   |
| <b>Floor:</b>                    | Checker Plate Steel                                                 |
| <b>Tongue Length:</b>            | 6' Models: 44"                                                      |
|                                  | 7' Modes: 52"                                                       |
| <b>Tie Downs:</b>                | Stake Pockets & Rub Rails<br>Perimeter D-Rings                      |
| <b>Spare Tire Mount:</b>         | Passenger Side- Removeable                                          |
| <b>Lights:</b>                   | Transport Canada & DOT Approved,<br>Sealed Beam LED                 |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                      |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                  |


### Models

|           |            |                      |
|-----------|------------|----------------------|
| SL610-10K | 72" x 120" | 981 kg (2,163 lbs)   |
| SL612-10K | 72" x 144" | 1,067 kg (2,348 lbs) |
| SL612-14K | 72" x 144" | 1,157 kg (2,546 lbs) |
| SL714-14K | 80" x 168" | 1,310 kg (2,882 lbs) |
| SL716-14K | 80" x 193" | 1,393 kg (3,064 lbs) |
| SL718-14K | 80" x 217" | 1,558 kg (3,428 lbs) |
| SL720-14K | 80" x 241" | 1,708 kg (3,758 lbs) |

### Popular Options

|                        |                    |
|------------------------|--------------------|
| Spare Tire             | Additional D-Rings |
| Lockable Steel Toolbox | Aluminum Wheels    |
| Hydraulic Brakes       | Heavy Floor        |
| Galvanize Trailer      |                    |

### Dealer Information & Pricing





## Single Axle Gravity Tilt Trailers



### Standard Features & Specifications

|                                  |                                                                                              |
|----------------------------------|----------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 5K: 2,360 kg (5,200 lbs)<br>7K: 3,175 kg (7,000 lbs)                                         |
| <b>Axle(s) &amp; Suspension:</b> | 5K: (1) 6,000 lbs Axle<br>7K: (1) 7,000 lbs Axle<br>w/Easy Lube Spindles, Torsion Suspension |
| <b>Tires:</b>                    | 5K: ST225/75R15 LRE Radial<br>7K: ST235/80R16 LRE Radial                                     |
| <b>Brakes:</b>                   | Electric on Both Axles                                                                       |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                                                 |
| <b>Jack:</b>                     | 7,000 lbs Drop Leg Jack                                                                      |
| <b>Deck Height:</b>              | 20"                                                                                          |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                        |
| <b>Tongue Length:</b>            | 50"                                                                                          |
| <b>Tie Downs:</b>                | Stake Pockets & (4) D-Rings                                                                  |
| <b>Spare Tire Mount:</b>         | Passenger Side- Removeable                                                                   |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                             |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                               |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                           |


### Models

|          |            |                    |
|----------|------------|--------------------|
| TL612-5K | 72" x 144" | 760 kg (1,673 lbs) |
| TL612-7K | 72" x 144" | 798 kg (1,755 lbs) |
| TL614-5K | 72" x 168" | 869 kg (1,912 lbs) |
| TL614-7K | 72" x 168" | 899 kg (1,978 lbs) |
| TL712-5K | 80" x 144" | 785 kg (1,726 lbs) |
| TL712-7K | 80" x 144" | 860 kg (1,892 lbs) |
| TL714-7K | 80" x 168" | 871 kg (1,916 lbs) |

### Popular Options

|                        |                    |
|------------------------|--------------------|
| Spare Tire             | Additional D-Rings |
| Lockable Steel Toolbox | Aluminum Wheels    |
| Hydraulic Brakes       | Heavy Floor        |
| Galvanize Trailer      |                    |

### Dealer Information & Pricing





# Gravity Tilt Trailers w/4ft Stationary Deck



### Standard Features & Specifications

|                                  |                                                                |
|----------------------------------|----------------------------------------------------------------|
| <b>GVWR:</b>                     | 6,858 kg (15,120 lbs)                                          |
| <b>Axle(s) &amp; Suspension:</b> | (2) 7,000 lb Axles<br>w/Easy Lube Spindles, Torsion Suspension |
| <b>Tires:</b>                    | ST235/80R16 LRE Radial                                         |
| <b>Brakes:</b>                   | Electric on Both Axles                                         |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                   |
| <b>Jack:</b>                     | 12,000 lbs Drop Leg Jack                                       |
| <b>Fenders:</b>                  | HD Fenders                                                     |
| <b>Deck Height:</b>              | 24"                                                            |
| <b>Stationary Deck:</b>          | 4'                                                             |
| <b>Tilt Features:</b>            | Gravity Tilt with Hydraulic Lock & Hydraulic Cushion Cylinder  |
| <b>Floor:</b>                    | Pressure Treated Wood                                          |
| <b>Tongue Length:</b>            | 52"                                                            |
| <b>Tie Downs:</b>                | Stake Pockets & Rub Rails                                      |
| <b>Spare Tire Mount:</b>         | Passenger Side- Removeable                                     |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED               |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                 |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                             |


### Models

|           |              |                      |
|-----------|--------------|----------------------|
| TL717-14K | 75.5" x 210" | 1,280 kg (2,815 lbs) |
| TL721-14K | 75.5" x 252" | 1,373 kg (3,020 lbs) |

### Popular Options

|                        |                   |
|------------------------|-------------------|
| Spare Tire             | Galvanize Trailer |
| Lockable Steel Toolbox | Aluminum Wheels   |
| Hydraulic Brakes       | Gooseneck         |
| D-Rings                |                   |

### Dealer Information & Pricing





## Electric Hydraulic Full Deck Tilt Trailers



### Standard Features & Specifications

|                                  |                                                                                                                                    |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 10K: 4,899 kg (10,800 lbs)<br>14K: 6,350 kg (15,120 lbs)<br>21KTR: 10,287 kg (22,680 lbs)                                          |
| <b>Axle(s) &amp; Suspension:</b> | 10K: (2) 6,000 lb Axles<br>14K: (2) 7,000 lb Axles<br>21KTR: (3) 7,000 lb Axles<br>w/Easy Lube Spindles, Slipper Spring Suspension |
| <b>Tires:</b>                    | 10K: ST225/75R15 LRE Radial<br>14K: ST235/80R16 LRE Radial<br>21KTR: ST235/80R16 LRE Radial                                        |
| <b>Brakes:</b>                   | Electric on All Axles                                                                                                              |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                                                                                       |
| <b>Jack:</b>                     | 12,000 lbs Drop Leg Jack                                                                                                           |
| <b>Fenders:</b>                  | HD Fenders                                                                                                                         |
| <b>Deck Height:</b>              | 24"                                                                                                                                |
| <b>Tilt Features:</b>            | Electric over Hydraulic Full Tilt<br>3" Hydraulic Cylinder<br>Interstate Extreme Cycle Battery<br>Lockable Steel Toolbox           |
| <b>Winch Plate:</b>              | Yes                                                                                                                                |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                                                              |
| <b>Tongue Length:</b>            | 52"                                                                                                                                |
| <b>Tie Downs:</b>                | Stake Pockets & Rub Rails                                                                                                          |
| <b>Spare Tire Mount:</b>         | Passenger Side- Removeable                                                                                                         |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                                                                   |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                                                                     |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                                                                 |


### Models

|              |            |                      |
|--------------|------------|----------------------|
| ETL718-10K   | 80" x 216" | 1,264 kg (2,780 lbs) |
| ETL720-10K   | 80" x 240" | 1,356 kg (2,984 lbs) |
| ETL718-14K   | 80" x 216" | 1,290 kg (2,838 lbs) |
| ETL720-14K   | 80" x 240" | 1,380 kg (3,036 lbs) |
| ETL722-14K   | 80" x 264" | 1,465 kg (3,222 lbs) |
| ETL724-14K   | 80" x 288" | 1,640 kg (3,608 lbs) |
| ETL724-21KTR | 80" x 288" | 1,934 kg (4,254 lbs) |

### Popular Options

|                  |                   |
|------------------|-------------------|
| Spare Tire       | Torsion Axles     |
| Hydraulic Brakes | Aluminum Wheels   |
| D-Rings          | Gooseneck         |
| 16K (2) 8K Axles | Galvanize Trailer |

### Dealer Information & Pricing





## Deck Over Hydraulic Power Tilt Trailers



### Standard Features & Specifications

|                                  |                                                                                                                                                                                                         |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 14K: 6,858 kg (15,120 lbs)<br>21KTR: 10,287 kg (22,680 lbs)                                                                                                                                             |
| <b>Axle(s) &amp; Suspension:</b> | 14K: (2) 7,000 lb Axles<br>21KTR: (3) 7000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension                                                                                                     |
| <b>Tires:</b>                    | ST235/80R16 LRE Radial                                                                                                                                                                                  |
| <b>Brakes:</b>                   | Electric on All Axles                                                                                                                                                                                   |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                                                                                                                                                            |
| <b>Jack:</b>                     | 12,000 lb Drop Leg Jack                                                                                                                                                                                 |
| <b>Deck Height:</b>              | 36"                                                                                                                                                                                                     |
| <b>Winch Plate:</b>              | Yes                                                                                                                                                                                                     |
| <b>Hoist Features:</b>           | Electric Over Hydraulic Full Deck Power Up/Power Down Tilt with Hand Remote. 5" Hydraulic Cylinder. Interstate Extreme Cycle Battery and Plug in Charger. Lockable Steel Toolbox. Pressure Treated Wood |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                                                                                                                                   |
| <b>Tongue Length:</b>            | 62"                                                                                                                                                                                                     |
| <b>Tie Downs:</b>                | Stake Pockets and Rub Rails                                                                                                                                                                             |
| <b>Spare Tire Mount:</b>         | Passenger Side of Box                                                                                                                                                                                   |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                                                                                                                                        |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                                                                                                                                          |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                                                                                                                                      |


### Models

|                |             |                      |
|----------------|-------------|----------------------|
| ETL822-14K     | 102" x 264" | 2,229 kg (4,904 lbs) |
| ETL824-14K     | 102" x 288" | 2,356 kg (5,580 lbs) |
| ETL826-14K     | 102" x 312" | 2,606 kg (5,734 lbs) |
| ETL824-21KTR   | 102" x 288" | 2,646 kg (5,822 lbs) |
| ETL826-21KTR   | 102" x 312" | 2,759 kg (6,070 lbs) |
| GNETL822-14K   | 102" x 264" | 2,349 kg (5,167 lbs) |
| GNETL824-14K   | 102" x 288" | 2,440 kg (5,367 lbs) |
| GNETL826-14K   | 102" x 312" | 2,553 kg (5,617 lbs) |
| GNETL824-21KTR | 102" x 288" | 2,631 kg (5,789 lbs) |
| GNETL826-21KTR | 102" x 312" | 2,790 kg (6,139 lbs) |

### Popular Options

|                         |                     |
|-------------------------|---------------------|
| Spare Tire              | D-Rings             |
| Hydraulic Brakes        | Sliding Winch Track |
| Galvanize Trailer       | Aluminum Wheels     |
| 16K: (2) 8,000 lb Axles |                     |

### Dealer Information & Pricing







## 102" Wide Hydraulic Full Deck Tilt Trailers



### Standard Features & Specifications

|                                  |                                                                                                                                    |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 14K: 6,350 kg (15,120 lbs)<br>16K: 7,855 kg (17,280 lbs)<br>21KTR: 10,287 kg (22,680 lbs)                                          |
| <b>Axle(s) &amp; Suspension:</b> | 14K: (2) 7,000 lb Axles<br>16K: (2) 8,000 lb Axles<br>21KTR: (3) 7,000 lb Axles<br>w/Easy Lube Spindles, Slipper Spring Suspension |
| <b>Tires:</b>                    | 14K: ST235/80R16 LRE Radial<br>16K: 215/75R17.5 LRH<br>21KTR: ST235/80R16 LRE Radial                                               |
| <b>Brakes:</b>                   | Electric on All Axles                                                                                                              |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                                                                                       |
| <b>Jack:</b>                     | 12,000 lbs Drop Leg Jack                                                                                                           |
| <b>Fenders:</b>                  | HD Drive Over Fenders                                                                                                              |
| <b>Deck Height:</b>              | 24"                                                                                                                                |
| <b>Tilt Features:</b>            | Electric over Hydraulic Full Tilt<br>3" Hydraulic Cylinder<br>Interstate Extreme Cycle Battery<br>Lockable Steel Toolbox           |
| <b>Winch Plate:</b>              | Yes                                                                                                                                |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                                                              |
| <b>Tongue Length:</b>            | 52"                                                                                                                                |
| <b>Tie Downs:</b>                | Stake Pockets, Rub Rails & 8 D-Rings                                                                                               |
| <b>Spare Tire Mount:</b>         | Passenger Side- Removeable                                                                                                         |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                                                                   |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                                                                     |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                                                                 |


### Models

|                 |             |                      |
|-----------------|-------------|----------------------|
| ETL102x18-14K   | 102" x 216" | 1,559 kg (3,429 lbs) |
| ETL102x20-14K   | 102" x 240" | 1,637 kg (3,602 lbs) |
| ETL102x22-14K   | 102" x 264" | 1,835 kg (4,036 lbs) |
| ETL102x24-14K   | 102" x 288" | 2,032 kg (4,470 lbs) |
| ETL102x26-14K   | 102" x 312" | 2,133 kg (4,692 lbs) |
| ETL102x18-16K   | 102" x 216" | 1,718 kg (3,779 lbs) |
| ETL102x20-16K   | 102" x 240" | 1,790 kg (3,937 lbs) |
| ETL102x22-16K   | 102" x 264" | 1,929 kg (4,244 lbs) |
| ETL102x24-16K   | 102" x 288" | 2,090 kg (4,598 lbs) |
| ETL102x26-16K   | 102" x 312" | 2,242 kg (4,932 lbs) |
| ETL102x24-21KTR | 102" x 288" | 2,153 kg (4,736 lbs) |

### Popular Options

|                  |                   |
|------------------|-------------------|
| Spare Tire       | Aluminum Wheels   |
| Hydraulic Brakes | Gooseneck         |
|                  | Galvanize Trailer |

### Dealer Information & Pricing





## 102" Wide Gooseneck Full Deck Tilt Trailers



### Standard Features & Specifications

|                                  |                                                                                                                                    |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 14K: 6,350 kg (15,120 lbs)<br>16K: 7,855 kg (17,280 lbs)<br>21KTR: 10,287 kg (22,680 lbs)                                          |
| <b>Axle(s) &amp; Suspension:</b> | 14K: (2) 7,000 lb Axles<br>16K: (2) 8,000 lb Axles<br>21KTR: (3) 7,000 lb Axles<br>w/Easy Lube Spindles, Slipper Spring Suspension |
| <b>Tires:</b>                    | 14K: ST235/80R16 LRE Radial<br>16K: 215/75R17.5 LRH<br>21KTR: ST235/80R16 LRE Radial                                               |
| <b>Brakes:</b>                   | Electric on All Axles                                                                                                              |
| <b>Coupler:</b>                  | Adjustable Gooseneck Coupler                                                                                                       |
| <b>Jack:</b>                     | 12,000 lbs Drop Leg Jack                                                                                                           |
| <b>Fenders:</b>                  | HD Drive Over Fenders                                                                                                              |
| <b>Deck Height:</b>              | 24"                                                                                                                                |
| <b>Tilt Features:</b>            | Electric over Hydraulic Full Tilt<br>3" Hydraulic Cylinder<br>Interstate Extreme Cycle Battery<br>Lockable Steel Toolbox           |
| <b>Winch Plate:</b>              | Yes                                                                                                                                |
| <b>Floor:</b>                    | Pressure Treated Wood & Steel                                                                                                      |
| <b>Gooseneck Length:</b>         | 9'                                                                                                                                 |
| <b>Tie Downs:</b>                | Stake Pockets, Rub Rails & 10 D-Rings                                                                                              |
| <b>Spare Tire Mount:</b>         | Passenger Side- Removeable                                                                                                         |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                                                                   |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                                                                     |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                                                                 |


### Models

|                   |             |                      |
|-------------------|-------------|----------------------|
| GNETL102x18-14K   | 102" x 216" | 1,967 kg (4,327 lbs) |
| GNETL102x20-14K   | 102" x 240" | 2,055 kg (4,522 lbs) |
| GNETL102x22-14K   | 102" x 264" | 2,232 kg (4,910 lbs) |
| GNETL102x24-14K   | 102" x 288" | 2,423 kg (5,331 lbs) |
| GNETL102x26-14K   | 102" x 312" | 2,580 kg (5,675 lbs) |
| GNETL102x18-16K   | 102" x 216" | 2,061 kg (4,535 lbs) |
| GNETL102x20-16K   | 102" x 240" | 2,148 kg (4,726 lbs) |
| GNETL102x22-16K   | 102" x 264" | 2,320 kg (5,104 lbs) |
| GNETL102x24-16K   | 102" x 288" | 2,507 kg (5,516 lbs) |
| GNETL102x26-16K   | 102" x 312" | 2,690 kg (5,918 lbs) |
| GNETL102x24-21KTR | 102" x 288" | 2,583 kg (5,683 lbs) |

### Popular Options

|                  |                   |
|------------------|-------------------|
| Spare Tire       | 16K (2) 8K Axles  |
| Hydraulic Brakes | Aluminum Wheels   |
| D-Rings          | Galvanize Trailer |

### Dealer Information & Pricing





## Heavy Duty Dump Trailers



### Standard Features & Specifications

|                                  |                                                                                                                                                                                                    |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 7K: 3,429 kg (7,560 lbs)<br>10K: 4,899 kg (10,800 lbs)                                                                                                                                             |
| <b>Axle(s) &amp; Suspension:</b> | 7K: (2) 3,500 lb Axles<br>10K: (2) 6,000 lb Axles<br>w/Easy Lube Spindles, Slipper Spring Suspension                                                                                               |
| <b>Tires:</b>                    | 7K: ST205/75R15 LRC Radial<br>10K: ST225/75R15 LRE Radial                                                                                                                                          |
| <b>Brakes:</b>                   | Electric on Both Axles                                                                                                                                                                             |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                                                                                                                                                       |
| <b>Jack:</b>                     | 7K Models: 7,000 lb Drop Leg Jack<br>10K Models: 12,000 lb Drop Leg Jack                                                                                                                           |
| <b>Fenders:</b>                  | HD Fenders                                                                                                                                                                                         |
| <b>Deck Height:</b>              | 22" - 27"                                                                                                                                                                                          |
| <b>Sides:</b>                    | 20" Steel & 10" Wood Plank                                                                                                                                                                         |
| <b>Doors:</b>                    | Barn Doors with Cam Lock                                                                                                                                                                           |
| <b>Load Cover:</b>               | Shielded Tarp and Roller                                                                                                                                                                           |
| <b>Hoist Features:</b>           | 3,000 psi Hydraulic Power Pack, 20' Hand Remote and Wireless Remote.<br>5" Hydraulic Cylinder & Scissor Hoist.<br>Interstate Extreme Cycle Battery and Plug in Charger.<br>Lockable Steel Toolbox. |
| <b>Floor:</b>                    | Steel                                                                                                                                                                                              |
| <b>Tongue Length:</b>            | 52"                                                                                                                                                                                                |
| <b>Tie Downs:</b>                | (4) Heavy Duty Welded In D-Rings                                                                                                                                                                   |
| <b>Spare Tire Mount:</b>         | Passenger Side of Box                                                                                                                                                                              |

|                         |                                                  |
|-------------------------|--------------------------------------------------|
| <b>Lights:</b>          | Transport Canada & DOT Approved, Sealed Beam LED |
| <b>Electrical/Plug:</b> | Sealed Harness & 7 Way RV Plug                   |
| <b>Finish:</b>          | Powder Coat & Scorpion Stone Guard               |

### Models

|             |                |                      |
|-------------|----------------|----------------------|
| DT510-7K    | 60" x 118.5"   | 1,241 kg (2,730 lbs) |
| DT610-7K    | 71.5" x 118.5" | 1,306 kg (2,874 lbs) |
| DT510-10K   | 60" x 118.5"   | 1,349 kg (2,967 lbs) |
| DT610-10K   | 71.5" x 118.5" | 1,399 kg (3,078 lbs) |
| DT612-10K   | 71.5" x 142.5" | 1,518 kg (3,340 lbs) |
| DT6.512-10K | 77.5" x 142.5" | 1,645 kg (3,620 lbs) |

### Popular Options

|                  |                                        |
|------------------|----------------------------------------|
| Spare Tire       | Additional D-Rings                     |
| Torsion Axles    | Hydraulic Brakes                       |
| Aluminum Wheels  | Two-Way Gate (Standard on DT6.512-10K) |
| Tarp Cover       | Galvanize Trailer (HD Floor Required)  |
| Rear Stabilizers |                                        |
| 48" Sides        |                                        |

### Dealer Information & Pricing





## Ultra Duty Dump Trailers



### Standard Features & Specifications

|                                  |                                                                                                                                                                                                                                                           |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 14K: 6,858 kg (15,120 lbs)<br>21KTR: 10,287 kg (22,680 lbs)                                                                                                                                                                                               |
| <b>Axle(s) &amp; Suspension:</b> | 14K: (2) 7,000 lb Axles<br>21KTR: (3) 7000 lb Axles<br>w/Easy Lube Spindles, Slipper Spring Suspension                                                                                                                                                    |
| <b>Tires:</b>                    | ST235/80R16 LRE Radial                                                                                                                                                                                                                                    |
| <b>Brakes:</b>                   | Electric on All Axles                                                                                                                                                                                                                                     |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or<br>3" Lunette Eye                                                                                                                                                                                                           |
| <b>Jack:</b>                     | 12,000 lb Drop Leg Jack                                                                                                                                                                                                                                   |
| <b>Fenders:</b>                  | HD Fenders                                                                                                                                                                                                                                                |
| <b>Deck Height:</b>              | 29"                                                                                                                                                                                                                                                       |
| <b>Sides:</b>                    | 20" steel + 10" Wood Plank                                                                                                                                                                                                                                |
| <b>Doors:</b>                    | Barn Doors with Cam Lock.<br>Two Way Gate.                                                                                                                                                                                                                |
| <b>Load Cover:</b>               | Shielded Tarp & Roller                                                                                                                                                                                                                                    |
| <b>Hoist Features:</b>           | 3,000 psi Hydraulic Power Pack, 20'<br>Hand Remote and Wireless Remote.<br>14K: 5" Hydraulic Cylinder<br>21KTR: 6" Hydraulic Cylinder, Both with<br>Scissor Hoist.<br>Interstate Extreme Cycle Battery and<br>Plug in Charger.<br>Lockable Steel Toolbox. |
| <b>Floor:</b>                    | Steel                                                                                                                                                                                                                                                     |
| <b>Tongue Length:</b>            | 52"                                                                                                                                                                                                                                                       |
| <b>Tie Downs:</b>                | 6' Models: (4), 83" Models: (6) Heavy<br>Duty Welded In D-Rings                                                                                                                                                                                           |
| <b>Spare Tire Mount:</b>         | Passenger Side of Box                                                                                                                                                                                                                                     |

|                         |                                                     |
|-------------------------|-----------------------------------------------------|
| <b>Lights:</b>          | Transport Canada & DOT Approved,<br>Sealed Beam LED |
| <b>Electrical/Plug:</b> | Sealed Harness & 7 Way RV Plug                      |
| <b>Finish:</b>          | Powder Coat & Scorpion Stone Guard                  |


### Models

|              |                |                      |
|--------------|----------------|----------------------|
| DT612-14K    | 71.5" x 142.5" | 1,669 kg (3,679 lbs) |
| DT8312-14K   | 83" x 142.5"   | 1,804 kg (3,968 lbs) |
| DT8314-14K   | 83" x 166.5"   | 2,086 kg (3,990 lbs) |
| DT8316-14K   | 83" x 190.5"   | 2,423 kg (5,341 lbs) |
| DT8314-21KTR | 83" x 166.5"   | 2,202 kg (4,844 lbs) |
| DT8316-21KTR | 83" x 190.5"   | 2,481 kg (5,458 lbs) |

### Popular Options

|                                 |                                          |
|---------------------------------|------------------------------------------|
| Spare Tire                      | Hydraulic Brakes                         |
| Additional D-Rings              | Aluminum Wheels                          |
| 5K or 8K Axle                   | Galvanize Trailer (Requires<br>HD Floor) |
| Torsion Axle                    |                                          |
| HD Floor (Required on<br>21KTR) |                                          |

### Dealer Information & Pricing





# Ultra Duty Deck Over Dump Trailers



## Standard Features & Specifications

|                                  |                                                                                                                                                                                               |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 14K: 6,858 kg (15,120 lbs)                                                                                                                                                                    |
|                                  | 16K: 7,855 kg (17,280 lbs)                                                                                                                                                                    |
|                                  | 21KTR: 10,287 kg (22,680 lbs)                                                                                                                                                                 |
|                                  | 24KD: 11,757 kg (25,920 lbs)                                                                                                                                                                  |
| <b>Axle(s) &amp; Suspension:</b> | 14K: (2) 7,000 lb Axles                                                                                                                                                                       |
|                                  | 16K: (2) 8,000 lb Axles                                                                                                                                                                       |
|                                  | 21KTR: (3) 7000 lb Axles w/Easy Lube Spindles, Slipper Spring                                                                                                                                 |
|                                  | 24KD: (2) 12,000 lb Axles, Dually w/Oil Bath Hubs, Slipper Spring Suspension                                                                                                                  |
| <b>Tires:</b>                    | 14K & 21KTR: ST235/80R16 LRE Radial                                                                                                                                                           |
|                                  | 16K: 215/75R17.5 LRH Radial                                                                                                                                                                   |
|                                  |                                                                                                                                                                                               |
| <b>Brakes:</b>                   | Electric on All Axles                                                                                                                                                                         |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                                                                                                                                                  |
| <b>Jack:</b>                     | 12,000 lb Drop Leg Jack                                                                                                                                                                       |
| <b>Deck Height:</b>              | 34-36"                                                                                                                                                                                        |
| <b>Sides:</b>                    | 20" Steel with 10" Wood Plank                                                                                                                                                                 |
| <b>Doors:</b>                    | Barn Doors with Cam Lock. Two Way Gate.                                                                                                                                                       |
| <b>Load Cover:</b>               | Shielded Tarp & Roller                                                                                                                                                                        |
| <b>Hoist Features:</b>           | 3,000 psi Hydraulic Power Pack, 20' Hand Remote and Wireless Remote. 6" Hydraulic Cylinder, with Scissor Hoist. Interstate Extreme Cycle Battery and Plug in Charger. Lockable Steel Toolbox. |
| <b>Floor:</b>                    | Steel (HD Floor Required on 16K & Up)                                                                                                                                                         |
| <b>Tongue Length:</b>            | 58"                                                                                                                                                                                           |
| <b>Tie Downs:</b>                | (6) Heavy Duty Welded In D-Rings                                                                                                                                                              |

|                         |                                                  |
|-------------------------|--------------------------------------------------|
| <b>Lights:</b>          | Transport Canada & DOT Approved, Sealed Beam LED |
| <b>Electrical/Plug:</b> | Sealed Harness & 7 Way RV Plug                   |
| <b>Finish:</b>          | Powder Coat & Scorpion Stone Guard               |

## Models

|             |              |                      |
|-------------|--------------|----------------------|
| DT814-14K   | 94" x 166.5" | 2,299 kg (5,058 lbs) |
| DT816-14K   | 94" x 190.5" | 2,663 kg (5,858 lbs) |
| DT816-16K   | 94" x 190.5" | 2,883 kg (6,344 lbs) |
| DT816-21KTR | 94" x 190.5" | 2,927 kg (6,440 lbs) |
| DT816-24KD  | 94" x 190.5" | 3,089 kg (6,796 lbs) |

## Popular Options

|                                  |                                               |
|----------------------------------|-----------------------------------------------|
| Spare Tire                       | Hydraulic Brakes                              |
| Additional D-Rings               | Aluminum Wheels                               |
| Torsion Axle (N/A on 16K & 24KD) | Galvanize Trailer (Requires HD Floor Upgrade) |
| Drop Sides                       |                                               |

## Dealer Information & Pricing





## Gooseneck Dump Trailers



### Standard Features & Specifications

|                                  |                                                                                                                                                                                                                                                         |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 14K: 6,858 kg (15,120 lbs)<br>21KTR: 10,287 kg (22,680 lbs)<br>24KD: 11,757 kg (25,920 lbs)                                                                                                                                                             |
| <b>Axle(s) &amp; Suspension:</b> | 14K: (2) 7,000 lb Axles<br>21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension<br>24KD: (2) 12,000 lb Axles w/Oil Bath Hubs, Slipper Spring Suspension                                                                            |
| <b>Tires:</b>                    | ST235/80R16 LRE Radial                                                                                                                                                                                                                                  |
| <b>Brakes:</b>                   | Electric on All Axles                                                                                                                                                                                                                                   |
| <b>Coupler:</b>                  | Adjustable Gooseneck Coupler                                                                                                                                                                                                                            |
| <b>Jack:</b>                     | (2) 12,000 lb Drop Leg Jacks                                                                                                                                                                                                                            |
| <b>Fenders:</b>                  | HD Fenders                                                                                                                                                                                                                                              |
| <b>Deck Height:</b>              | 7' Model: 29"<br>8' Model: 36"                                                                                                                                                                                                                          |
| <b>Sides:</b>                    | 20" steel + 10" Wood Plank                                                                                                                                                                                                                              |
| <b>Doors:</b>                    | Barn Doors with Cam Lock.<br>Two Way Gate.                                                                                                                                                                                                              |
| <b>Load Cover:</b>               | Shielded Tarp & Roller                                                                                                                                                                                                                                  |
| <b>Hoist Features:</b>           | 3,000 psi Hydraulic Power Pack, 20' Hand Remote and Wireless Remote.<br>14K: 5" Hydraulic Cylinder<br>21KTR & 24KD: 6" Hydraulic Cylinder, Both with Scissor Hoist.<br>Interstate Extreme Cycle Battery and Plug in Charger.<br>Lockable Steel Toolbox. |
| <b>Floor:</b>                    | Steel (16K & Up Require HD Floor)                                                                                                                                                                                                                       |
| <b>Tongue Length:</b>            | 52"                                                                                                                                                                                                                                                     |
| <b>Tie Downs:</b>                | (6) Heavy Duty Welded In D-Rings                                                                                                                                                                                                                        |
| <b>Spare Tire Mount:</b>         | Passenger Side of Box                                                                                                                                                                                                                                   |

|                         |                                                  |
|-------------------------|--------------------------------------------------|
| <b>Lights:</b>          | Transport Canada & DOT Approved, Sealed Beam LED |
| <b>Electrical/Plug:</b> | Sealed Harness & 7 Way RV Plug                   |
| <b>Finish:</b>          | Powder Coat & Scorpion Stone Guard               |


### Models

|                |              |                      |
|----------------|--------------|----------------------|
| GNDT8314-14K   | 83" x 166.5" | 2,296 kg (5,052 lbs) |
| GNDT8316-14K   | 83" x 190.5" | 2,700 kg (5,941 lbs) |
| GNDT8314-21KTR | 83" x 166.5" | 2,631 kg (5,788 lbs) |
| GNDT8316-21KTR | 83" x 190.5" | 2,806 kg (6,174 lbs) |
| GNDT814-14K    | 94" x 166.5" | 2,680 kg (5,895 lbs) |
| GNDT816-14K    | 94" x 190.5" | 3,020 kg (6,644 lbs) |
| GNDT816-21KTR  | 94" x 190.5" | 3,472 kg (7,638 lbs) |
| GNDT816-24KD   | 94" x 190.5" | 4,040 kg (8,888 lbs) |

### Popular Options

|                                       |                              |
|---------------------------------------|------------------------------|
| Spare Tire                            | Additional D-Rings           |
| Galvanize Trailer (Requires HD Floor) | HD Floor (Required on 21KTR) |
| Hydraulic Brakes                      | 6' Ramps                     |
| 48" High Sides                        | 16K: (2) 8,000 lb Axles      |
| Aluminum Wheels, N/A on 16K & 24KD    | Rear Stabilizers             |

### Dealer Information & Pricing





## Straight Deck Pintle Series Trailers



### Standard Features & Specifications

|                                  |                                                                                                                                                            |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 7K: 3,429 kg (7,560 lbs)<br>10K: 4,899 kg (10,800 lbs)<br>14K: 6,858 kg (15,120 lbs)<br>21KTR: 10,287 kg (22,680 lbs)                                      |
| <b>Axle(s) &amp; Suspension:</b> | 7K: (2) 3,500 lb Axles<br>10K: (2) 6,000 lb Axles<br>14K: (2) 7,000 lb Axles<br>21KTR: (3) 7,000 lb Axles, w/Easy Lube Spindles, Slipper Spring Suspension |
| <b>Tires:</b>                    | 7K: ST205/75R15 LRC Radial<br>10K: ST225/75R15 LRE Radial<br>14K & 21KTR: ST235/80R16 LRE Radial                                                           |
| <b>Brakes:</b>                   | Electric on All Axles                                                                                                                                      |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                                                                                                               |
| <b>Jack:</b>                     | 12,000 lbs Drop Leg Jack                                                                                                                                   |
| <b>Ramps:</b>                    | 7' Ramps, Stowed Under Deck                                                                                                                                |
| <b>Deck Height:</b>              | 7K & 10K: 32"<br>14K – 24KD: 36"                                                                                                                           |
| <b>Frame:</b>                    | Light Weight, Rigid Frame<br>Crossmembers every 16"                                                                                                        |
| <b>Side Steps:</b>               | On Both Sides                                                                                                                                              |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                                                                                      |
| <b>Tongue Length:</b>            | 62"                                                                                                                                                        |
| <b>Tie Downs:</b>                | Stake Pockets & Rub Rails                                                                                                                                  |
| <b>Spare Tire Mount:</b>         | Optional – Tongue Mount Only                                                                                                                               |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                                                                                           |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                                                                                             |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                                                                                         |


### Models

|            |             |                      |
|------------|-------------|----------------------|
| SD16-7K    | 102" x 192" | 1,340 kg (2,948 lbs) |
| SD18-7K    | 102" x 216" | 1,370 kg (3,015 lbs) |
| SD20-7K    | 102" x 240" | 1,458 kg (3,208 lbs) |
| SD16-10K   | 102" x 192" | 1,608 kg (3,538 lbs) |
| SD18-10K   | 102" x 216" | 1,672 kg (3,680 lbs) |
| SD20-10K   | 102" x 240" | 1,730 kg (3,808 lbs) |
| SD16-14K   | 102" x 192" | 1,580 kg (3,476 lbs) |
| SD18-14K   | 102" x 216" | 1,677 kg (3,690 lbs) |
| SD20-14K   | 102" x 240" | 1,742 kg (3,832 lbs) |
| SD24-14K   | 102" x 288" | 1,845 kg (4,060 lbs) |
| SD28-14K   | 102" x 336" | 2,228 kg (4,902 lbs) |
| SD24-21KTR | 102" x 288" | 2,154 kg (4,740 lbs) |
| SD28-21KTR | 102" x 336" | 2,356 kg (5,184 lbs) |
| SD30-21KTR | 102" x 360" | 2,499 kg (5,498 lbs) |

### Popular Options

|                      |                                 |
|----------------------|---------------------------------|
| Spare Tire           | Dual 12K Jacks                  |
| Winch Track          | Hydraulic Brakes                |
| Sliding Winch & Stap | D-Rings                         |
| Galvanize Trailer    | Torsion Axles, Not              |
| 16K – Two 8K Axles   | Available on 24KD & 30KD        |
| 24KD – Two 12K Axles | Aluminum Wheels, Not            |
| 30KD – Two 15K Axles | Available on 16K, 24KD and 30KD |

### Dealer Information & Pricing







## Straight Deck Gooseneck Series Trailers



### Standard Features & Specifications

|                                  |                                                                                                                                                                                     |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 14K: 6,858 kg (15,120 lbs)<br>21KTR: 10,287 kg (22,680 lbs)<br>24KD: 10,890 kg (25,920 lbs)                                                                                         |
| <b>Axle(s) &amp; Suspension:</b> | 14K: (2) 7,000 lb Axles<br>21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension<br>24KD: (2) 12,000 lb Axle, Dually w/Oil Bath Hubs, Slipper Spring Suspension |
| <b>Tires:</b>                    | ST235/80R16 LRE Radial                                                                                                                                                              |
| <b>Brakes:</b>                   | Electric on All Axles                                                                                                                                                               |
| <b>Coupler:</b>                  | Adjustable Gooseneck Coupler                                                                                                                                                        |
| <b>Jack:</b>                     | (2) 12,000 lb Drop Leg Jacks                                                                                                                                                        |
| <b>Ramps:</b>                    | 7' Ramps, Stowed Under Deck                                                                                                                                                         |
| <b>Deck Height:</b>              | 36"                                                                                                                                                                                 |
| <b>Frame:</b>                    | Light Weight, Rigid Frame<br>Crossmembers every 16"                                                                                                                                 |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                                                                                                               |
| <b>Side Steps:</b>               | On Both Sides                                                                                                                                                                       |
| <b>Gooseneck Length:</b>         | 9'                                                                                                                                                                                  |
| <b>Tie Downs:</b>                | Stake Pockets & Rub Rails                                                                                                                                                           |
| <b>Spare Tire Mount:</b>         | On Gooseneck                                                                                                                                                                        |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                                                                                                                    |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                                                                                                                      |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                                                                                                                  |


### Models

|              |             |                      |
|--------------|-------------|----------------------|
| GNSD20-14K   | 102" x 240" | 2,125 kg (4,636 lbs) |
| GNSD24-14K   | 102" x 288" | 2,210 kg (4,861 lbs) |
| GNSD24-21KTR | 102" x 288" | 2,437 kg (5,362 lbs) |
| GNSD28-21KTR | 102" x 336" | 2,627 kg (5,779 lbs) |
| GNSD30-21KTR | 102" x 360" | 2,703 kg (6,236 lbs) |
| GNSD32-21KTR | 102" x 384" | 2,965 kg (6,523 lbs) |
| GNSD24-24KD  | 102" x 288" | 2,835 kg (6,238 lbs) |
| GNSD28-24KD  | 102" x 336" | 2,981 kg (6,558 lbs) |
| GNSD30-24KD  | 102" x 360" | 3,124 kg (6,872 lbs) |
| GNSD32-24KD  | 102" x 384" | 3,231 kg (7,108 lbs) |

### Popular Options

|                      |                    |
|----------------------|--------------------|
| Spare Tire           | Torsion Axles, Not |
| Winch Track          | Available on 24KD  |
| Sliding Winch & Stap | Hydraulic Brakes   |
| King Pin             | D-Rings            |
| 16K – Two 8K Axles   | Aluminum Wheels    |
| 30KD–Two 15K Axles   | Galvanize Trailer  |

### Dealer Information & Pricing







## Beavertail Deck Over Pintle Series Trailers



### Standard Features & Specifications

|                                  |                                                                            |
|----------------------------------|----------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 14K: 6,858 kg (15,120 lbs)                                                 |
| <b>Axle(s) &amp; Suspension:</b> | 14K: (2) 7,000 lb Axles<br>w/Easy Lube Spindles, Slipper Spring Suspension |
| <b>Tires:</b>                    | ST235/80R16 LRE Radial                                                     |
| <b>Brakes:</b>                   | Electric on All Axles                                                      |
| <b>Coupler:</b>                  | Adjustable 2-5/16" Coupler or 3" Lunette Eye                               |
| <b>Jack:</b>                     | 12,000 lbs Drop Leg Jack                                                   |
| <b>Beavertail:</b>               | 5' Beavertail with Wood Floor                                              |
| <b>Ramps:</b>                    | 5' Spring Assisted Wedge Ramps                                             |
| <b>Deck Height:</b>              | 36"                                                                        |
| <b>Frame:</b>                    | Light Weight, Rigid Frame<br>Crossmembers every 16"                        |
| <b>Floor:</b>                    | Pressure Treated Wood                                                      |
| <b>Tongue Length:</b>            | 62"                                                                        |
| <b>Tie Downs:</b>                | Stake Pockets & Rub Rails                                                  |
| <b>Side Steps:</b>               | On Both Sides                                                              |
| <b>Spare Tire Mount:</b>         | Optional – Tongue Mount Only                                               |
| <b>Lights:</b>                   | Transport Canada & DOT Approved,<br>Sealed Beam LED                        |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                             |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                         |


### Models

|          |             |                      |
|----------|-------------|----------------------|
| BT22-14K | 102" x 264" | 2,051 kg (4,512 lbs) |
| BT25-14K | 102" x 300" | 2,198 kg (4,836 lbs) |

### Popular Options

|                        |                  |
|------------------------|------------------|
| Spare Tire             | Hydraulic Brakes |
| Lockable Steel Toolbox | D-Rings          |
| Galvanize Trailer      | Aluminum Wheels  |
| Full Width Ramps       | Dual 12K Jacks   |
| 16K – Two 8K Axles     |                  |

### Dealer Information & Pricing





## Premium Pintle Series Trailers



### Standard Features & Specifications

|                                  |                                                                                                                                                                                     |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 14K: 6,858 kg (15,120 lbs)<br>21KTR: 10,287 kg (22,680 lbs)<br>24KD: 11,757 kg (25,920 lbs)                                                                                         |
| <b>Axle(s) &amp; Suspension:</b> | 14K: (2) 7,000 lb Axles<br>21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension<br>24KD: (2) 12,000 lb Axle, Dually w/Oil Bath Hubs, Slipper Spring Suspension |
| <b>Tires:</b>                    | ST235/80R16 LRE Radial                                                                                                                                                              |
| <b>Brakes:</b>                   | Electric on All Axles                                                                                                                                                               |
| <b>Coupler:</b>                  | Adjustable 3" Lunette Eye                                                                                                                                                           |
| <b>Jack:</b>                     | 12,000 lb Drop Leg Jack                                                                                                                                                             |
| <b>Ramps:</b>                    | Full Width Ramps                                                                                                                                                                    |
| <b>Deck Height:</b>              | 36"                                                                                                                                                                                 |
| <b>Frame:</b>                    | 12" @ 22 lbs. Heavy Wide-Flange Beams.<br>Crossmembers every 16".                                                                                                                   |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                                                                                                               |
| <b>Tongue Length:</b>            | 62"                                                                                                                                                                                 |
| <b>Beavertail:</b>               | 5' Angle Iron Beavertail                                                                                                                                                            |
| <b>Tie Downs:</b>                | Stake Pockets & Rub Rails                                                                                                                                                           |
| <b>Side Steps:</b>               | On Both Sides                                                                                                                                                                       |
| <b>Winch Track:</b>              | Driver's Side                                                                                                                                                                       |
| <b>Spare Tire Mount:</b>         | Optional – Tongue Mount Only                                                                                                                                                        |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                                                                                                                    |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                                                                                                                      |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                                                                                                                  |


### Models

|              |             |                      |
|--------------|-------------|----------------------|
| PHFT22-14K   | 102" x 264" | 2,370 kg (5,215 lbs) |
| PHFT25-14K   | 102" x 300" | 2,560 kg (5,632 lbs) |
| PHFT28-14K   | 102" x 336" | 2,743 kg (6,035 lbs) |
| PHFT30-14K   | 102" x 360" | 2,888 kg (6,354 lbs) |
| PHFT25-21KTR | 102" x 300" | 2,837 kg (6,241 lbs) |
| PHFT28-21KTR | 102" x 336" | 2,979 kg (6,554 lbs) |
| PHFT30-21KTR | 102" x 360" | 3,065 kg (6,742 lbs) |
| PHFT32-21KTR | 102" x 384" | 3,297 kg (7,254 lbs) |
| PHFT25-24KD  | 102" x 300" | 3,026 kg (6,657 lbs) |
| PHFT28-24KD  | 102" x 336" | 3,208 kg (7,057 lbs) |
| PHFT30-24KD  | 102" x 360" | 3,355 kg (7,381 lbs) |
| PHFT32-24KD  | 102" x 384" | 3,463 kg (7,618 lbs) |

### Popular Options

|                                      |                                         |
|--------------------------------------|-----------------------------------------|
| Torsion Axles, Not Available on 24KD | Aluminum Wheels – Not Available on 24KD |
| Spare Tire                           | D-Rings                                 |
| 6' Tongue                            | Hydraulic Brakes                        |
| Dual 12K lb Jacks                    | 16K – Two 8K Axles                      |
| Lockable Steel Toolbox               | 30KD-Two 15K Axles                      |
| Galvanize Trailer                    |                                         |

### Dealer Information & Pricing





## Premium Gooseneck Series Trailers



### Standard Features & Specifications

|                                  |                                                                                                                                                                                      |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 14K: 6,858 kg (15,120 lbs)<br>21KTR: 10,287 kg (22,680 lbs)<br>24KD: 11,757 kg (25,920 lbs)                                                                                          |
| <b>Axle(s) &amp; Suspension:</b> | 14K: (2) 7,000 lb Axles<br>21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension.<br>24KD: (2) 12,000 lb Axle, Dually w/Oil Bath Hubs, Slipper Spring Suspension |
| <b>Tires:</b>                    | ST235/80R16 LRE Radial                                                                                                                                                               |
| <b>Brakes:</b>                   | Electric on All Axles                                                                                                                                                                |
| <b>Coupler:</b>                  | Adjustable Gooseneck Coupler                                                                                                                                                         |
| <b>Jack:</b>                     | (2) 12,000 lb Drop Leg Jack                                                                                                                                                          |
| <b>Ramps:</b>                    | 5' Full Width Ramps                                                                                                                                                                  |
| <b>Deck Height:</b>              | 36"                                                                                                                                                                                  |
| <b>Frame:</b>                    | 12" @ 22 lbs. Heavy Wide-Flange Beams.<br>Crossmembers every 16".                                                                                                                    |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                                                                                                                |
| <b>Gooseneck Length:</b>         | 9'                                                                                                                                                                                   |
| <b>Beavertail:</b>               | 5' Angle Iron Beavertail                                                                                                                                                             |
| <b>Tie Downs:</b>                | Stake Pockets & Rub Rails                                                                                                                                                            |
| <b>Side Steps:</b>               | On Both Sides                                                                                                                                                                        |
| <b>Winch Track:</b>              | Driver's Side                                                                                                                                                                        |
| <b>Spare Tire Mount:</b>         | On Gooseneck                                                                                                                                                                         |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                                                                                                                     |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                                                                                                                       |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                                                                                                                   |

### Models

|              |             |                      |
|--------------|-------------|----------------------|
| GNFT25-14K   | 102" x 300" | 2,786 kg (6,129 lbs) |
| GNFT28-14K   | 102" x 336" | 2,946 kg (6,481 lbs) |
| GNFT30-14K   | 102" x 360" | 3,285 kg (7,227 lbs) |
| GNFT32-14K   | 102" x 384" | 3,418 kg (7,519 lbs) |
| GNFT25-21KTR | 102" x 300" | 3,115 kg (6,854 lbs) |
| GNFT28-21KTR | 102" x 336" | 3,415 kg (7,514 lbs) |
| GNFT30-21KTR | 102" x 360" | 3,608 kg (7,938 lbs) |
| GNFT32-21KTR | 102" x 384" | 3,755 kg (8,260 lbs) |
| GNFT25-24KD  | 102" x 300" | 3,424 kg (7,533 lbs) |
| GNFT28-24KD  | 102" x 336" | 3,605 kg (7,930 lbs) |
| GNFT30-24KD  | 102" x 360" | 3,722 kg (8,190 lbs) |
| GNFT32-24KD  | 102" x 384" | 3,829 kg (8,424 lbs) |

### Popular Options

|                                              |                                      |
|----------------------------------------------|--------------------------------------|
| Aluminum Wheels, Not Available on 16K & 24KD | Torsion Axles, Not Available on 24KD |
| King Pin                                     | Hydraulic Brakes                     |
| Spare Tire                                   | D-Rings                              |
| 16K – Two 8K Axles                           | Galvanize Trailer                    |
| 30KD-Two 15K Axles                           |                                      |

### Dealer Information & Pricing





## Gooseneck XD Series Trailers



### Standard Features & Specifications

|                                  |                                                                                                                |
|----------------------------------|----------------------------------------------------------------------------------------------------------------|
| <b>GVWR:</b>                     | 24KD: 11,757 kg (25,920 lbs)<br>30KD: 13,636 kg (30,000 lbs)                                                   |
| <b>Axle(s) &amp; Suspension:</b> | 24KD: (2) 12,000 lb Axles, Dually<br>30KD: (2) 15,000 lb Axles, Dually w/Oil Bath Hubs, Hutch Suspension       |
| <b>Tires:</b>                    | 24KD: ST235/80R16 LRE Radial<br>30KD: ST215/75R15 LRH Radial                                                   |
| <b>Brakes:</b>                   | Electric on All Axles                                                                                          |
| <b>Coupler:</b>                  | Adjustable Gooseneck Coupler                                                                                   |
| <b>Jack:</b>                     | 12,000 lb 2 Speed Jacks                                                                                        |
| <b>Ramps:</b>                    | 5' Full Width Ramps                                                                                            |
| <b>Deck Height:</b>              | 36"                                                                                                            |
| <b>Frame:</b>                    | 12" @ 22 lbs. Wide Flange Pierced I-Beam Frame. Torque Tube. Crossmembers every 16". HD 1/4" Plate over Axles. |
| <b>Floor:</b>                    | Pressure Treated Wood                                                                                          |
| <b>Gooseneck Length:</b>         | 9'                                                                                                             |
| <b>Beavertail:</b>               | 5' Angle Iron Beavertail                                                                                       |
| <b>Tie Downs:</b>                | Stake Pockets & Rub Rails                                                                                      |
| <b>Side Steps:</b>               | On Both Sides                                                                                                  |
| <b>Winch Track:</b>              | Driver's Side                                                                                                  |
| <b>Spare Tire Mount:</b>         | On Gooseneck                                                                                                   |
| <b>Loading Lights:</b>           | Rear Facing w/ Remote On/Off                                                                                   |
| <b>Lights:</b>                   | Transport Canada & DOT Approved, Sealed Beam LED                                                               |
| <b>Electrical/Plug:</b>          | Sealed Harness & 7 Way RV Plug                                                                                 |
| <b>Finish:</b>                   | Powder Coat & Scorpion Stone Guard                                                                             |

### Models

|             |             |                       |
|-------------|-------------|-----------------------|
| GNXD30-24KD | 102" x 360" | 3,989 kg (8,775 lbs)  |
| GNXD32-24KD | 102" x 384" | 4,205 kg (9,251 lbs)  |
| GNXD35-24KD | 102" x 420" | 4,375 kg (9,624 lbs)  |
| GNXD40-24KD | 102" x 480" | 4,750 kg (10,450 lbs) |
| GNXD30-30KD | 102" x 360" | 4,086 kg (8,990 lbs)  |
| GNXD32-30KD | 102" x 384" | 4,243 kg (9,335 lbs)  |
| GNXD35-30KD | 102" x 420" | 4,720 kg (10,384 lbs) |
| GNXD40-30KD | 102" x 480" | 4,932 kg (10,850 lbs) |

### Popular Options

|            |                  |
|------------|------------------|
| King Pin   | Hydraulic Brakes |
| Spare Tire |                  |

### Dealer Information & Pricing







# **CANADA TRAILERS**

## **Canada Trailers Manufacturing Limited**

11918 Imperial Road, Hwy. 73  
Aylmer Ontario  
N5H 2R3

Phone: 519-765-1717

Fax: 519-765-1725

**[www.canadatrailers.com](http://www.canadatrailers.com)**