



CANADA TRAILERS



Canada Trailers Manufacturing Limited

11918 Imperial Road, Hwy. 73

Aylmer Ontario

N5H 2R3

Phone: 519-765-1717

Fax: 519-765-1725

www.canadatrailers.com



Table of Contents

Trailer Model	Page #
Single Axle Steel Side Utility Trailers	1
Tandem Axle Steel Side Landscape/Utility Trailers	2
H.D. Tandem Axle Steel Side Landscape/Utility Trailers	3
Car Trailers	4
Equipment Trailers	5
Gooseneck Equipment Trailers	6
102" Wide Equipment Trailers w/ 4' Max Ramps	7
102" Wide Gooseneck Equipment Trailers w/ 4' Max Ramps	8
Low Incline Scissor Lift Trailers	9
Single Axle Gravity Tilt Trailers	10
Gravity Tilt Trailers w/ 4' Stationary Deck	11
Electric Hydraulic Full Deck Tilt Trailers	12
Deck Over Hydraulic Power Tilt Trailers	13
102" Wide Hydraulic Full Deck Tilt Trailers	14
102" Wide Gooseneck Hyd. Full Deck Tilt Trailers	15
Heavy Duty Dump Trailers	16
Ultra Duty Dump Trailers	17
Ultra Duty Deck Over Dump Trailers	18
Gooseneck Dump Trailers	19
Straight Deck Pintle Series Trailers	20
Straight Deck Gooseneck Series Trailers	21
Beavertail Deck Over Pintle Series Trailers	22
Premium Pintle Series Trailers	23
Premium Gooseneck Series Trailers	24
Gooseneck XD Series Trailers	25



Single Axle Steel Side Utility Trailers



Standard Features & Specifications

GVWR:	3K: 1,356 kg (2,990 lbs) 3.5K: 1,587 kg (3,500 lbs) 5K: 2,267 kg (5,000 lbs)
Axle(s) & Suspension:	3K & 3.5K: (1) 3,500 lb Axle w/Easy Lube Spindles, Double Eye Spring Suspension 5K: (1) 5,200 lb Axle w/ same
Tires:	3K & 3.5K: ST205/75R15 LRC Radial 5K: ST225/75R15 LRE Radial
Brakes:	Electric
Coupler:	2" A-Frame Coupler
Jack:	3 & 3.5K: 2,000 lbs A-Frame Jack 5K: 5,000 lbs A-Frame Jack
Deck Height:	17"
Sides:	15" Solid Steel + 3" Tie Rail
Ramp:	3 & 3.5K: 4' Straight Ramp w/ Mesh 5K: Spring Assisted Ramps
Floor:	Pressure Treated Wood
Tongue Length:	5' Models : 42" 6' Models : 46" 7' Models : 48"
Tie Downs:	(4) Welded In D-Rings
Spare Tire Mount:	Front of Bed, Upright
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	3K: Sealed Harness & 4 Way Flat Plug 3.5K & 5K: 7 Way RV Plug
Finish:	Powder Coat – Matte Black


Models

UT58-3K	60.5" x 98"	423 kg (930 lbs)
UT510-3K	60.5" x 122"	472 kg (1,038 lbs)
UT512-3K	60.5" x 146"	518 kg (1,141 lbs)
UT514-3K	60.5" x 170"	556 kg (1,224 lbs)
UT610-3K	72" x 122"	567 kg (1,248 lbs)
UT612-3K	72" x 146"	605 kg (1,332 lbs)
UT712-3.5K	82" x 146"	666 kg (1,466 lbs)
UT714-3.5K	82" x 170"	714 kg (1,571 lbs)
UT712-5K	82" x 146"	752 kg (1,654 lbs)
UT714-5K	82" x 170"	858 kg (1,888 lbs)

Popular Options

Bifold Ramp (5ft & 6ft only)	Galvanize Trailer
Additional D-Rings	Aluminum Wheels
5K Axle	

Dealer Information & Pricing





Tandem Axle Steel Side Landscape/Utility Trailers



Standard Features & Specifications

GVWR:	3,429 kg (7,560 lbs)
Axle(s) & Suspension:	(2) 3,500 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	ST205/75R15 LRC Radial
Brakes:	Electric on Both Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	7,000 lbs A-Frame Jack
Fenders:	HD Fenders
Deck Height:	19"
Sides:	15" Solid Steel + 3" Tie Rail
Ramps:	4' Split Ramps w/ Mesh
Floor:	Pressure Treated Wood
Tongue Length:	53"
Tie Downs:	Stake Pockets Welded In D-Rings
Spare Tire Mount:	Front of Bed, Upright
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

UT712-7K	82" x 145"	879 kg (1,934 lbs)
UT714-7K	82" x 169"	898 kg (1,976 lbs)
UT716-7K	82" x 193"	982 kg (2,160 lbs)
UT718-7K	82" x 217"	1,012 kg (2,226 lbs)
UT720-7K	82" x 241"	1,070 kg (2,354 lbs)

Popular Options

Spare Tire	Torsion Axles
Lockable Steel Toolbox	Additional D-Rings
7000 lbs Drop Leg Jack	Aluminum Wheels
Rear Stabilizers	Galvanize Trailer
Side ATV Ramps	

Dealer Information & Pricing





H.D. Tandem Axle Steel Side Landscape/Utility Trailers



Standard Features & Specifications

GVWR:	10K: 4,899 kg (10,800 lbs) 14K: 6,858 kg (15,120 lbs)
Axle(s) & Suspension:	10K: (2) 6,000 lb Axles 14K: (2) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	10K: ST225/75R15 LRE Radial 14K: ST235/80R16 LRE Radial
Brakes:	Electric on Both Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lbs Drop Leg Jack
Fenders:	HD Fenders
Deck Height:	20"
Sides:	15" Solid Steel + 3" Tie Rail
Ramps:	5' Heavy Duty Spring Assisted Split Ramps w/ Mesh
Floor:	Pressure Treated Wood
Tongue Length:	53"
Tie Downs:	Stake Pockets Welded In D-Rings
Spare Tire Mount:	Front of Bed, Upright
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

UT716-10K	82" x 193"	1,201 kg (2,642 lbs)
UT718-10K	82" x 217"	1,245 kg (2,738 lbs)
UT720-10K	82" x 241"	1,378 kg (3,032 lbs)
UT722-10K	82" x 265"	1,442 kg (3,174 lbs)
UT724-10K	82" x 288"	1,511 kg (3,326 lbs)
UT716-14K	82" x 193"	1,355 kg (2,982 lbs)
UT718-14K	82" x 217"	1,420 kg (3,124 lbs)
UT720-14K	82" x 241"	1,508 kg (3,318 lbs)
UT722-14K	82" x 265"	1,615 kg (3,553 lbs)
UT724-14K	82" x 288"	1,688 kg (3,714 lbs)

Popular Options

Spare Tire	Torsion Axles
Lockable Steel Toolbox	Additional D-Rings
Hydraulic Brakes	Aluminum Wheels
Rear Stabilizers	Galvanize Trailer

Dealer Information & Pricing





Standard Features & Specifications

GVWR:	3,429 kg (7,560 lbs)
Axle(s) & Suspension:	(2) 3,500 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	ST205/75R15 LRC Radial
Brakes:	Electric on Both Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	7,000 lbs A-Frame Jack
Fenders:	HD Fenders
Deck Height:	23"
Sides:	2' with Wood Floor
Ramps:	4' Ramps – Stored Under Deck
Floor:	Pressure Treated Wood
Tongue Length:	53"
Tie Downs:	Stake Pockets
Spare Tire Mount:	Passenger Side- Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

CE714-7K	82" x 168"	951 kg (2,092 lbs)
CE716-7K	82" x 192"	982 kg (2,160 lbs)
CE718-7K	82" x 216"	1,013 kg (2,228 lbs)
CE720-7K	82" x 240"	1,083 kg (2,382 lbs)

Popular Options

Spare Tire	Torsion Axles
Lockable Steel Toolbox	Straight Deck
7000 lbs Drop Leg Jack	Aluminum Wheels
4' Beaver Tail	Galvanize Trailer
5' Spring Assisted Up-right Ramps	Hydraulic Brakes

Dealer Information & Pricing





Standard Features & Specifications

GVWR:	10K: 4,899 kg (10,800 lbs) 14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs)
Axle(s) & Suspension:	10K: (2) 5,200 lb Axles 14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	10K: ST225/75R15 LRE Radial 14K & 21KTR: ST235/80R16 LRE Radial
Brakes:	Electric on all Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lbs Drop Leg Jack
Fenders:	HD Fenders
Deck Height:	24"
Beavertail:	2' with Wood Floor
Ramps:	5' Spring Assisted Up-right Ramps
Floor:	Pressure Treated Wood
Tongue Length:	52"
Tie Downs:	Stake Pockets & Rub Rails
Spare Tire Mount:	Passenger Side- Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard

Models

CE714-10K	83" x 168"	1,092 kg (2,403 lbs)
CE716-10K	83" x 192"	1,173 kg (2,580 lbs)
CE718-10K	83" x 216"	1,251 kg (2,752 lbs)
CE720-10K	83" x 240"	1,339 kg (2,946 lbs)
CE714-14K	83" x 168"	1,163 kg (2,559 lbs)
CE716-14K	83" x 192"	1,224 kg (2,692 lbs)
CE718-14K	83" x 216"	1,303 kg (2,867 lbs)
CE720-14K	83" x 240"	1,348 kg (2,966 lbs)
CE722-14K	83" x 264"	1,457 kg (3,205 lbs)
CE724-14K	83" x 288"	1,523 kg (3,350 lbs)
CE720-21KTR	83" x 240"	1,795 kg (3,950 lbs)
CE722-21KTR	83" x 264"	1,831 kg (4,028 lbs)
CE724-21KTR	83" x 288"	1,873 kg (4,120 lbs)

Popular Options

Spare Tire	Torsion Axles
Lockable Steel Toolbox	8K Axles
5' Extra Wide Ramps	Aluminum Wheels
Hydraulic Brakes	Galvanize Trailer
102" Wide w/ Stand-up or Pull-out Ramps	Straight Deck

Dealer Information & Pricing





Gooseneck Equipment Trailers



Standard Features & Specifications

GVWR:	14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	ST235/80R16 LRE Radial
Brakes:	Electric on all Axles
Coupler:	Adjustable Gooseneck Coupler
Jack:	12,000 lbs Drop Leg Jack
Fenders:	HD Fenders
Deck Height:	24"
Beavertail:	2' with Wood Floor
Ramps:	5' Spring Assisted Up-right Ramps
Floor:	Pressure Treated Wood
Gooseneck Length:	9'
Tie Downs:	Stake Pockets & Rub Rails
Spare Tire Mount:	Passenger Side - Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

GNCE720-14K	83" x 240"	1,871 kg (4,116 lbs)
GNCE722-14K	83" x 264"	1,970 kg (4,355 lbs)
GNCE724-14K	83" x 288"	2,045 kg (4,500 lbs)
GNCE726-14K	83" x 312"	2,117 kg (4,658 lbs)
GNCE728-14K	83" x 336"	2,210 kg (4,861 lbs)
GNCE720-21KTR	83" x 240"	2,318 kg (5,100 lbs)
GNCE722-21KTR	83" x 264"	2,354 kg (5,178 lbs)
GNCE724-21KTR	83" x 288"	2,395 kg (5,270 lbs)
GNCE726-21KTR	83" x 312"	2,514 kg (5,530 lbs)
GNCE728-21KTR	83" x 336"	2,630 kg (5,785 lbs)
GNCE732-21KTR	83" x 384"	2,791 kg (6,140 lbs)

Popular Options

Spare Tire	Torsion Axles
Lockable Steel Toolbox	8K Axles
5' Extra Wide Ramps	Aluminum Wheels
Winch Plate	Galvanize Trailer
Hydraulic Brakes	Straight Deck
102" Wide w/ Stand-up or Pull-out Ramps	

Dealer Information & Pricing





102" Equipment Trailers w/4' Max Ramps



Standard Features & Specifications

GVWR:	14K: 6,858 kg (15,120 lbs)
	16K: 7,855 kg (17,280 lbs)
	21KTR: 10,287 kg (22,680 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles
	16K: (2) 8,000 lb Axles
	21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	14K: ST235/80R16 LRE Radial
	16K: 215/75R17.5 LRH Radial
	21KTR: ST235/80R16 LRE Radial
Brakes:	Electric on all Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lbs Drop Leg Jack
Fenders:	HD Drive Over Fenders
Deck Height:	24"
Beavertail:	4' with Wood Floor
Ramps:	4' Spring Assisted Fold Flat Mega Ramps
Floor:	Pressure Treated Wood
Tongue Length:	52"
Tie Downs:	Stake Pockets, Rub Rails & D-Rings
Spare Tire Mount:	Passenger Side - Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

CE102x22-14K	102" x 264"	1,713 kg (3,769 lbs)
CE102x24-14K	102" x 288"	1,805 kg (3,971 lbs)
CE102x26-14K	102" x 312"	1,905 kg (4,191 lbs)
CE102x22-16K	102" x 264"	1,871 kg (4,116 lbs)
CE102x24-16K	102" x 288"	1,974 kg (4,342 lbs)
CE102x26-16K	102" x 312"	2,089 kg (4,595 lbs)
CE102x26-21KTR	102" x 312"	2,215 kg (4,873 lbs)
CE102x28-21KTR	102" x 336"	2,422 kg (5,329 lbs)
CE102x32-21KTR	102" x 384"	2,564 kg (5,640 lbs)

Popular Options

Spare Tire	Galvanize Trailer
Lockable Steel Toolbox	Aluminum Wheels
Hydraulic Brakes	Straight Deck
Gooseneck	Additional D-Rings

Dealer Information & Pricing





102" Gooseneck Equip. Trailers w/4' Max Ramps



Standard Features & Specifications

GVWR:	14K: 6,858 kg (15,120 lbs) 16K: 7,855 kg (17,280 lbs) 21KTR: 10,287 kg (22,680 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles 16K: (2) 8,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	14K: ST235/80R16 LRE Radial 16K: 215/75R17.5 LRH Radial 21KTR: ST235/80R16 LRE Radial
Brakes:	Electric on all Axles
Coupler:	Adjustable Gooseneck Coupler
Jack:	12,000 lbs Drop Leg Jacks
Fenders:	HD Drive Over Fenders
Deck Height:	24"
Beavertail:	4' with Wood Floor
Ramps:	4' Spring Assisted Fold Flat Mega Ramps
Floor:	Pressure Treated Wood
Winch Plate:	Yes, Raised Between Gooseneck
Gooseneck Length:	9'
Tie Downs:	Stake Pockets, Rub Rails & D-Rings
Spare Tire Mount:	Passenger Side- Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

GNCE102x22-14K	102" x 264"	2,225 kg (4,895 lbs)
GNCE102x24-14K	102" x 288"	2,308 kg (5,078 lbs)
GNCE102x26-14K	102" x 312"	2,434 kg (5,354 lbs)
GNCE102x22-16K	102" x 264"	2,291 kg (5,040 lbs)
GNCE102x24-16K	102" x 288"	2,420 kg (5,325 lbs)
GNCE102x26-16K	102" x 312"	2,643 kg (5,815 lbs)
GNCE102x26-21KTR	102" x 312"	2,607 kg (5,736 lbs)
GNCE102x28-21KTR	102" x 336"	2,708 kg (5,958 lbs)
GNCE102x32-21KTR	102" x 384"	2,943 kg (6,475 lbs)

Popular Options

Spare Tire	Aluminum Wheels
Additional D-Rings	Galvanize Trailer
Hydraulic Brakes	Straight Deck

Dealer Information & Pricing





Low Incline Scissor Lift Trailers



Standard Features & Specifications

GVWR:	10K: 4,899 kg (10,800 lbs)
	14K: 6,858 kg (15,120 lbs)
Axle(s) & Suspension:	10K: (2) 6,000 lb Axles
	14K: (2) 7,000 lb Axles w/Easy Lube Spindles, Torsion Suspension
Tires:	10K: ST225/75R15 LRE Radial
	14K: ST235/80R16 LRE Radial
Brakes:	Electric on Both Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lbs Drop Leg Jack (2) 7,000 lbs Rear Stabilizing Jacks
Fenders:	HD Fenders
Deck Height:	15"
Ramps:	5' Spring Assisted Up-right Ramps
Floor:	Checker Plate Steel
Tongue Length:	6' Models: 44"
	7' Modes: 52"
Tie Downs:	Stake Pockets & Rub Rails Perimeter D-Rings
Spare Tire Mount:	Passenger Side- Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

SL610-10K	72" x 120"	981 kg (2,163 lbs)
SL612-10K	72" x 144"	1,067 kg (2,348 lbs)
SL612-14K	72" x 144"	1,157 kg (2,546 lbs)
SL714-14K	80" x 168"	1,310 kg (2,882 lbs)
SL716-14K	80" x 193"	1,393 kg (3,064 lbs)
SL718-14K	80" x 217"	1,558 kg (3,428 lbs)
SL720-14K	80" x 241"	1,708 kg (3,758 lbs)

Popular Options

Spare Tire	Additional D-Rings
Lockable Steel Toolbox	Aluminum Wheels
Hydraulic Brakes	Heavy Floor
Galvanize Trailer	

Dealer Information & Pricing





Single Axle Gravity Tilt Trailers



Standard Features & Specifications

GVWR:	5K: 2,360 kg (5,200 lbs) 7K: 3,175 kg (7,000 lbs)
Axle(s) & Suspension:	5K: (1) 6,000 lbs Axle 7K: (1) 7,000 lbs Axle w/Easy Lube Spindles, Torsion Suspension
Tires:	5K: ST225/75R15 LRE Radial 7K: ST235/80R16 LRE Radial
Brakes:	Electric on Both Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	7,000 lbs Drop Leg Jack
Deck Height:	20"
Floor:	Pressure Treated Wood
Tongue Length:	50"
Tie Downs:	Stake Pockets & (4) D-Rings
Spare Tire Mount:	Passenger Side- Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

TL612-5K	72" x 144"	760 kg (1,673 lbs)
TL612-7K	72" x 144"	798 kg (1,755 lbs)
TL614-5K	72" x 168"	869 kg (1,912 lbs)
TL614-7K	72" x 168"	899 kg (1,978 lbs)
TL712-5K	80" x 144"	785 kg (1,726 lbs)
TL712-7K	80" x 144"	860 kg (1,892 lbs)
TL714-7K	80" x 168"	871 kg (1,916 lbs)

Popular Options

Spare Tire	Additional D-Rings
Lockable Steel Toolbox	Aluminum Wheels
Hydraulic Brakes	Heavy Floor
Galvanize Trailer	

Dealer Information & Pricing





Gravity Tilt Trailers w/4ft Stationary Deck



Standard Features & Specifications

GVWR:	6,858 kg (15,120 lbs)
Axle(s) & Suspension:	(2) 7,000 lb Axles w/Easy Lube Spindles, Torsion Suspension
Tires:	ST235/80R16 LRE Radial
Brakes:	Electric on Both Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lbs Drop Leg Jack
Fenders:	HD Fenders
Deck Height:	24"
Stationary Deck:	4'
Tilt Features:	Gravity Tilt with Hydraulic Lock & Hydraulic Cushion Cylinder
Floor:	Pressure Treated Wood
Tongue Length:	52"
Tie Downs:	Stake Pockets & Rub Rails
Spare Tire Mount:	Passenger Side- Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

TL717-14K	75.5" x 210"	1,280 kg (2,815 lbs)
TL721-14K	75.5" x 252"	1,373 kg (3,020 lbs)

Popular Options

Spare Tire	Galvanize Trailer
Lockable Steel Toolbox	Aluminum Wheels
Hydraulic Brakes	Gooseneck
D-Rings	

Dealer Information & Pricing





Electric Hydraulic Full Deck Tilt Trailers



Standard Features & Specifications

GVWR:	10K: 4,899 kg (10,800 lbs) 14K: 6,350 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs)
Axle(s) & Suspension:	10K: (2) 6,000 lb Axles 14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	10K: ST225/75R15 LRE Radial 14K: ST235/80R16 LRE Radial 21KTR: ST235/80R16 LRE Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lbs Drop Leg Jack
Fenders:	HD Fenders
Deck Height:	24"
Tilt Features:	Electric over Hydraulic Full Tilt 3" Hydraulic Cylinder Interstate Extreme Cycle Battery Lockable Steel Toolbox
Winch Plate:	Yes
Floor:	Pressure Treated Wood
Tongue Length:	52"
Tie Downs:	Stake Pockets & Rub Rails
Spare Tire Mount:	Passenger Side- Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

ETL718-10K	80" x 216"	1,264 kg (2,780 lbs)
ETL720-10K	80" x 240"	1,356 kg (2,984 lbs)
ETL718-14K	80" x 216"	1,290 kg (2,838 lbs)
ETL720-14K	80" x 240"	1,380 kg (3,036 lbs)
ETL722-14K	80" x 264"	1,465 kg (3,222 lbs)
ETL724-14K	80" x 288"	1,640 kg (3,608 lbs)
ETL724-21KTR	80" x 288"	1,934 kg (4,254 lbs)

Popular Options

Spare Tire	Torsion Axles
Hydraulic Brakes	Aluminum Wheels
D-Rings	Gooseneck
16K (2) 8K Axles	Galvanize Trailer

Dealer Information & Pricing





Deck Over Hydraulic Power Tilt Trailers



Standard Features & Specifications

GVWR:	14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles 21KTR: (3) 7000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	ST235/80R16 LRE Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lb Drop Leg Jack
Deck Height:	36"
Winch Plate:	Yes
Hoist Features:	Electric Over Hydraulic Full Deck Power Up/Power Down Tilt with Hand Remote. 5" Hydraulic Cylinder. Interstate Extreme Cycle Battery and Plug in Charger. Lockable Steel Toolbox. Pressure Treated Wood
Floor:	Pressure Treated Wood
Tongue Length:	62"
Tie Downs:	Stake Pockets and Rub Rails
Spare Tire Mount:	Passenger Side of Box
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

ETL822-14K	102" x 264"	2,229 kg (4,904 lbs)
ETL824-14K	102" x 288"	2,356 kg (5,580 lbs)
ETL826-14K	102" x 312"	2,606 kg (5,734 lbs)
ETL824-21KTR	102" x 288"	2,646 kg (5,822 lbs)
ETL826-21KTR	102" x 312"	2,759 kg (6,070 lbs)
GNETL822-14K	102" x 264"	2,349 kg (5,167 lbs)
GNETL824-14K	102" x 288"	2,440 kg (5,367 lbs)
GNETL826-14K	102" x 312"	2,553 kg (5,617 lbs)
GNETL824-21KTR	102" x 288"	2,631 kg (5,789 lbs)
GNETL826-21KTR	102" x 312"	2,790 kg (6,139 lbs)

Popular Options

Spare Tire	D-Rings
Hydraulic Brakes	Sliding Winch Track
Galvanize Trailer	Aluminum Wheels
16K: (2) 8,000 lb Axles	

Dealer Information & Pricing





102" Wide Hydraulic Full Deck Tilt Trailers



Standard Features & Specifications

GVWR:	14K: 6,350 kg (15,120 lbs) 16K: 7,855 kg (17,280 lbs) 21KTR: 10,287 kg (22,680 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles 16K: (2) 8,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	14K: ST235/80R16 LRE Radial 16K: 215/75R17.5 LRH 21KTR: ST235/80R16 LRE Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lbs Drop Leg Jack
Fenders:	HD Drive Over Fenders
Deck Height:	24"
Tilt Features:	Electric over Hydraulic Full Tilt 3" Hydraulic Cylinder Interstate Extreme Cycle Battery Lockable Steel Toolbox
Winch Plate:	Yes
Floor:	Pressure Treated Wood
Tongue Length:	52"
Tie Downs:	Stake Pockets, Rub Rails & 8 D-Rings
Spare Tire Mount:	Passenger Side- Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

ETL102x18-14K	102" x 216"	1,559 kg (3,429 lbs)
ETL102x20-14K	102" x 240"	1,637 kg (3,602 lbs)
ETL102x22-14K	102" x 264"	1,835 kg (4,036 lbs)
ETL102x24-14K	102" x 288"	2,032 kg (4,470 lbs)
ETL102x26-14K	102" x 312"	2,133 kg (4,692 lbs)
ETL102x18-16K	102" x 216"	1,718 kg (3,779 lbs)
ETL102x20-16K	102" x 240"	1,790 kg (3,937 lbs)
ETL102x22-16K	102" x 264"	1,929 kg (4,244 lbs)
ETL102x24-16K	102" x 288"	2,090 kg (4,598 lbs)
ETL102x26-16K	102" x 312"	2,242 kg (4,932 lbs)
ETL102x24-21KTR	102" x 288"	2,153 kg (4,736 lbs)

Popular Options

Spare Tire	Aluminum Wheels
Hydraulic Brakes	Gooseneck
	Galvanize Trailer

Dealer Information & Pricing





102" Wide Gooseneck Full Deck Tilt Trailers



Standard Features & Specifications

GVWR:	14K: 6,350 kg (15,120 lbs) 16K: 7,855 kg (17,280 lbs) 21KTR: 10,287 kg (22,680 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles 16K: (2) 8,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	14K: ST235/80R16 LRE Radial 16K: 215/75R17.5 LRH 21KTR: ST235/80R16 LRE Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable Gooseneck Coupler
Jack:	12,000 lbs Drop Leg Jack
Fenders:	HD Drive Over Fenders
Deck Height:	24"
Tilt Features:	Electric over Hydraulic Full Tilt 3" Hydraulic Cylinder Interstate Extreme Cycle Battery Lockable Steel Toolbox
Winch Plate:	Yes
Floor:	Pressure Treated Wood & Steel
Gooseneck Length:	9'
Tie Downs:	Stake Pockets, Rub Rails & 10 D-Rings
Spare Tire Mount:	Passenger Side- Removeable
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

GNETL102x18-14K	102" x 216"	1,967 kg (4,327 lbs)
GNETL102x20-14K	102" x 240"	2,055 kg (4,522 lbs)
GNETL102x22-14K	102" x 264"	2,232 kg (4,910 lbs)
GNETL102x24-14K	102" x 288"	2,423 kg (5,331 lbs)
GNETL102x26-14K	102" x 312"	2,580 kg (5,675 lbs)
GNETL102x18-16K	102" x 216"	2,061 kg (4,535 lbs)
GNETL102x20-16K	102" x 240"	2,148 kg (4,726 lbs)
GNETL102x22-16K	102" x 264"	2,320 kg (5,104 lbs)
GNETL102x24-16K	102" x 288"	2,507 kg (5,516 lbs)
GNETL102x26-16K	102" x 312"	2,690 kg (5,918 lbs)
GNETL102x24-21KTR	102" x 288"	2,583 kg (5,683 lbs)

Popular Options

Spare Tire	16K (2) 8K Axles
Hydraulic Brakes	Aluminum Wheels
D-Rings	Galvanize Trailer

Dealer Information & Pricing





Heavy Duty Dump Trailers



Standard Features & Specifications

GVWR:	7K: 3,429 kg (7,560 lbs) 10K: 4,899 kg (10,800 lbs)
Axle(s) & Suspension:	7K: (2) 3,500 lb Axles 10K: (2) 6,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	7K: ST205/75R15 LRC Radial 10K: ST225/75R15 LRE Radial
Brakes:	Electric on Both Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	7K Models: 7,000 lb Drop Leg Jack 10K Models: 12,000 lb Drop Leg Jack
Fenders:	HD Fenders
Deck Height:	22" - 27"
Sides:	20" Steel & 10" Wood Plank
Doors:	Barn Doors with Cam Lock
Load Cover:	Shielded Tarp and Roller
Hoist Features:	3,000 psi Hydraulic Power Pack, 20' Hand Remote and Wireless Remote. 5" Hydraulic Cylinder & Scissor Hoist. Interstate Extreme Cycle Battery and Plug in Charger. Lockable Steel Toolbox.
Floor:	Steel
Tongue Length:	52"
Tie Downs:	(4) Heavy Duty Welded In D-Rings
Spare Tire Mount:	Passenger Side of Box

Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard

Models

DT510-7K	60" x 118.5"	1,241 kg (2,730 lbs)
DT610-7K	71.5" x 118.5"	1,306 kg (2,874 lbs)
DT510-10K	60" x 118.5"	1,349 kg (2,967 lbs)
DT610-10K	71.5" x 118.5"	1,399 kg (3,078 lbs)
DT612-10K	71.5" x 142.5"	1,518 kg (3,340 lbs)
DT6.512-10K	77.5" x 142.5"	1,645 kg (3,620 lbs)

Popular Options

Spare Tire	Additional D-Rings
Torsion Axles	Hydraulic Brakes
Aluminum Wheels	Two-Way Gate (Standard on DT6.512-10K)
Tarp Cover	Galvanize Trailer (HD Floor Required)
Rear Stabilizers	
48" Sides	

Dealer Information & Pricing





Ultra Duty Dump Trailers



Standard Features & Specifications

GVWR:	14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles 21KTR: (3) 7000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	ST235/80R16 LRE Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lb Drop Leg Jack
Fenders:	HD Fenders
Deck Height:	29"
Sides:	20" steel + 10" Wood Plank
Doors:	Barn Doors with Cam Lock. Two Way Gate.
Load Cover:	Shielded Tarp & Roller
Hoist Features:	3,000 psi Hydraulic Power Pack, 20' Hand Remote and Wireless Remote. 14K: 5" Hydraulic Cylinder 21KTR: 6" Hydraulic Cylinder, Both with Scissor Hoist. Interstate Extreme Cycle Battery and Plug in Charger. Lockable Steel Toolbox.
Floor:	Steel
Tongue Length:	52"
Tie Downs:	6' Models: (4), 83" Models: (6) Heavy Duty Welded In D-Rings
Spare Tire Mount:	Passenger Side of Box

Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

DT612-14K	71.5" x 142.5"	1,669 kg (3,679 lbs)
DT8312-14K	83" x 142.5"	1,804 kg (3,968 lbs)
DT8314-14K	83" x 166.5"	2,086 kg (3,990 lbs)
DT8316-14K	83" x 190.5"	2,423 kg (5,341 lbs)
DT8314-21KTR	83" x 166.5"	2,202 kg (4,844 lbs)
DT8316-21KTR	83" x 190.5"	2,481 kg (5,458 lbs)

Popular Options

Spare Tire	Hydraulic Brakes
Additional D-Rings	Aluminum Wheels
Rear Stabilizers	Galvanize Trailer (Requires HD Floor)
Ramps	
HD Floor (Required on 21KTR)	

Dealer Information & Pricing





Ultra Duty Deck Over Dump Trailers



Standard Features & Specifications

GVWR:	14K: 6,858 kg (15,120 lbs) 16K: 7,855 kg (17,280 lbs) 21KTR: 10,287 kg (22,680 lbs) 24KD: 11,757 kg (25,920 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles 16K: (2) 8,000 lb Axles 21KTR: (3) 7000 lb Axles w/Easy Lube Spindles, Slipper Spring 24KD: (2) 12,000 lb Axles, Dually w/Oil Bath Hubs, Slipper Spring Suspension
Tires:	14K & 21KTR: ST235/80R16 LRE Radial 16K: 215/75R17.5 LRH Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lb Drop Leg Jack
Deck Height:	34-36"
Sides:	20" Steel with 10" Wood Plank
Doors:	Barn Doors with Cam Lock. Two Way Gate.
Load Cover:	Shielded Tarp & Roller
Hoist Features:	3,000 psi Hydraulic Power Pack, 20' Hand Remote and Wireless Remote. 6" Hydraulic Cylinder, with Scissor Hoist. Interstate Extreme Cycle Battery and Plug in Charger. Lockable Steel Toolbox.
Floor:	Steel (HD Floor Required on 16K & Up)
Tongue Length:	58"
Tie Downs:	(6) Heavy Duty Welded In D-Rings

Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

DT814-14K	94" x 166.5"	2,299 kg (5,058 lbs)
DT816-14K	94" x 190.5"	2,663 kg (5,858 lbs)
DT816-16K	94" x 190.5"	2,883 kg (6,344 lbs)
DT816-21KTR	94" x 190.5"	2,927 kg (6,440 lbs)
DT816-24KD	94" x 190.5"	3,089 kg (6,796 lbs)

Popular Options

Spare Tire	Hydraulic Brakes
Additional D-Rings	Aluminum Wheels
48" High Sides	Galvanize Trailer (Requires
7' Ramps	HD Floor Upgrade)
Drop Sides	

Dealer Information & Pricing





Gooseneck Dump Trailers



Standard Features & Specifications

GVWR:	14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs) 24KD: 11,757 kg (25,920 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension 24KD: (2) 12,000 lb Axles w/Oil Bath Hubs, Slipper Spring Suspension
Tires:	ST235/80R16 LRE Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable Gooseneck Coupler
Jack:	(2) 12,000 lb Drop Leg Jacks
Fenders:	HD Fenders
Deck Height:	7' Model: 29" 8' Model: 36"
Sides:	20" steel x 10" Wood Plank
Doors:	Barn Doors with Cam Lock. Two Way Gate.
Load Cover:	Shielded Tarp & Roller
Hoist Features:	3,000 psi Hydraulic Power Pack, 20' Hand Remote and Wireless Remote. 14K: 5" Hydraulic Cylinder 21KTR & 24KD: 6" Hydraulic Cylinder, Both with Scissor Hoist. Interstate Extreme Cycle Battery and Plug in Charger. Lockable Steel Toolbox.
Floor:	Steel (16K & Up Require HD Floor)
Tongue Length:	52"
Tie Downs:	(6) Heavy Duty Welded In D-Rings
Spare Tire Mount:	Passenger Side of Box

Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard

Models

GNDT8314-14K	83" x 166.5"	2,296 kg (5,052 lbs)
GNDT8316-14K	83" x 190.5"	2,700 kg (5,941 lbs)
GNDT8314-21KTR	83" x 166.5"	2,631 kg (5,788 lbs)
GNDT8316-21KTR	83" x 190.5"	2,806 kg (6,174 lbs)
GNDT814-14K	94" x 166.5"	2,680 kg (5,895 lbs)
GNDT816-14K	94" x 190.5"	3,020 kg (6,644 lbs)
GNDT816-21KTR	94" x 190.5"	3,472 kg (7,638 lbs)
GNDT816-24KD	94" x 190.5"	4,040 kg (8,888 lbs)

Popular Options

Spare Tire	Additional D-Rings
Galvanize Trailer (Requires HD Floor)	HD Floor (Required on 21KTR)
Hydraulic Brakes	6' Ramps
48" High Sides	16K: (2) 8,000 lb Axles
Aluminum Wheels, N/A on 16K & 24KD	Rear Stabilizers, N/A on Deck Over Models

Dealer Information & Pricing





Straight Deck Pintle Series Trailers



Standard Features & Specifications

GVWR:	7K: 3,429 kg (7,560 lbs) 10K: 4,899 kg (10,800 lbs) 14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs)
Axle(s) & Suspension:	7K: (2) 3,500 lb Axles 10K: (2) 6,000 lb Axles 14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles, w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	7K: ST205/75R15 LRC Radial 10K: ST225/75R15 LRE Radial 14K & 21KTR: ST235/80R16 LRE Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lbs Drop Leg Jack
Ramps:	7' Ramps, Stowed Under Deck
Deck Height:	7K & 10K: 32" 14K – 24KD: 36"
Frame:	Light Weight, Rigid Frame Crossmembers every 16"
Side Steps:	On Both Sides
Floor:	Pressure Treated Wood
Tongue Length:	62"
Tie Downs:	Stake Pockets & Rub Rails
Spare Tire Mount:	Optional – Tongue Mount Only
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

SD16-7K	102" x 192"	1,340 kg (2,948 lbs)
SD18-7K	102" x 216"	1,370 kg (3,015 lbs)
SD20-7K	102" x 240"	1,458 kg (3,208 lbs)
SD16-10K	102" x 192"	1,608 kg (3,538 lbs)
SD18-10K	102" x 216"	1,672 kg (3,680 lbs)
SD20-10K	102" x 240"	1,730 kg (3,808 lbs)
SD16-14K	102" x 192"	1,580 kg (3,476 lbs)
SD18-14K	102" x 216"	1,677 kg (3,690 lbs)
SD20-14K	102" x 240"	1,742 kg (3,832 lbs)
SD24-14K	102" x 288"	1,845 kg (4,060 lbs)
SD28-14K	102" x 336"	2,228 kg (4,902 lbs)
SD24-21KTR	102" x 288"	2,154 kg (4,740 lbs)
SD28-21KTR	102" x 336"	2,356 kg (5,184 lbs)
SD30-21KTR	102" x 360"	2,499 kg (5,498 lbs)

Popular Options

Spare Tire	Dual 12K Jacks
Winch Track	Hydraulic Brakes
Sliding Winch & Stap	D-Rings
Galvanize Trailer	Torsion Axles, Not
16K – Two 8K Axles	Available on 24KD & 30KD
24KD – Two 12K Axles	Aluminum Wheels, Not
30KD – Two 15K Axles	Available on 16K, 24KD and 30KD

Dealer Information & Pricing





Straight Deck Gooseneck Series Trailers



Standard Features & Specifications

GVWR:	14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs) 24KD: 10,890 kg (25,920 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension 24KD: (2) 12,000 lb Axle, Dually w/Oil Bath Hubs, Slipper Spring Suspension
Tires:	ST235/80R16 LRE Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable Gooseneck Coupler
Jack:	(2) 12,000 lb Drop Leg Jacks
Ramps:	7' Ramps, Stowed Under Deck
Deck Height:	36"
Frame:	Light Weight, Rigid Frame Crossmembers every 16"
Floor:	Pressure Treated Wood
Side Steps:	On Both Sides
Gooseneck Length:	9'
Tie Downs:	Stake Pockets & Rub Rails
Spare Tire Mount:	On Gooseneck
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

GNSD20-14K	102" x 240"	2,125 kg (4,636 lbs)
GNSD24-14K	102" x 288"	2,210 kg (4,861 lbs)
GNSD24-21KTR	102" x 288"	2,437 kg (5,362 lbs)
GNSD28-21KTR	102" x 336"	2,627 kg (5,779 lbs)
GNSD30-21KTR	102" x 360"	2,703 kg (6,236 lbs)
GNSD32-21KTR	102" x 384"	2,965 kg (6,523 lbs)
GNSD24-24KD	102" x 288"	2,835 kg (6,238 lbs)
GNSD28-24KD	102" x 336"	2,981 kg (6,558 lbs)
GNSD30-24KD	102" x 360"	3,124 kg (6,872 lbs)
GNSD32-24KD	102" x 384"	3,231 kg (7,108 lbs)

Popular Options

Spare Tire	Torsion Axles, Not
Winch Track	Available on 24KD
Sliding Winch & Stap	Hydraulic Brakes
King Pin	D-Rings
16K – Two 8K Axles	Aluminum Wheels
30KD–Two 15K Axles	Galvanize Trailer

Dealer Information & Pricing





Beavertail Deck Over Pintle Series Trailers



Standard Features & Specifications

GVWR:	14K: 6,858 kg (15,120 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension
Tires:	ST235/80R16 LRE Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lbs Drop Leg Jack
Beavertail:	5' Beavertail with Wood Floor
Ramps:	5' Spring Assisted Wedge Ramps
Deck Height:	36"
Frame:	Light Weight, Rigid Frame Crossmembers every 16"
Floor:	Pressure Treated Wood
Tongue Length:	62"
Tie Downs:	Stake Pockets & Rub Rails
Side Steps:	On Both Sides
Spare Tire Mount:	Optional – Tongue Mount Only
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

BT22-14K	102" x 264"	2,051 kg (4,512 lbs)
BT25-14K	102" x 300"	2,198 kg (4,836 lbs)

Popular Options

Spare Tire	Hydraulic Brakes
Lockable Steel Toolbox	D-Rings
Galvanize Trailer	Aluminum Wheels
Full Width Ramps	Dual 12K Jacks
16K – Two 8K Axles	

Dealer Information & Pricing





Premium Pintle Series Trailers



Standard Features & Specifications

GVWR:	14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs) 24KD: 11,757 kg (25,920 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension 24KD: (2) 12,000 lb Axle, Dually w/Oil Bath Hubs, Slipper Spring Suspension
Tires:	ST235/80R16 LRE Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable 3" Lunette Eye
Jack:	12,000 lb Drop Leg Jack
Ramps:	Full Width Ramps
Deck Height:	36"
Frame:	12" @ 22 lbs. Heavy Wide-Flange Beams. Crossmembers every 16".
Floor:	Pressure Treated Wood
Tongue Length:	62"
Beavertail:	5' Angle Iron Beavertail
Tie Downs:	Stake Pockets & Rub Rails
Side Steps:	On Both Sides
Winch Track:	Driver's Side
Spare Tire Mount:	Optional – Tongue Mount Only
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

PHFT22-14K	102" x 264"	2,370 kg (5,215 lbs)
PHFT25-14K	102" x 300"	2,560 kg (5,632 lbs)
PHFT28-14K	102" x 336"	2,743 kg (6,035 lbs)
PHFT30-14K	102" x 360"	2,888 kg (6,354 lbs)
PHFT25-21KTR	102" x 300"	2,837 kg (6,241 lbs)
PHFT28-21KTR	102" x 336"	2,979 kg (6,554 lbs)
PHFT30-21KTR	102" x 360"	3,065 kg (6,742 lbs)
PHFT32-21KTR	102" x 384"	3,297 kg (7,254 lbs)
PHFT25-24KD	102" x 300"	3,026 kg (6,657 lbs)
PHFT28-24KD	102" x 336"	3,208 kg (7,057 lbs)
PHFT30-24KD	102" x 360"	3,355 kg (7,381 lbs)
PHFT32-24KD	102" x 384"	3,463 kg (7,618 lbs)

Popular Options

Torsion Axles, Not Available on 24KD	Aluminum Wheels – Not Available on 24KD
Spare Tire	D-Rings
6' Tongue	Hydraulic Brakes
Dual 12K lb Jacks	16K – Two 8K Axles
Lockable Steel Toolbox	30KD-Two 15K Axles
Galvanize Trailer	

Dealer Information & Pricing





Premium Gooseneck Series Trailers



Standard Features & Specifications

GVWR:	14K: 6,858 kg (15,120 lbs) 21KTR: 10,287 kg (22,680 lbs) 24KD: 11,757 kg (25,920 lbs)
Axle(s) & Suspension:	14K: (2) 7,000 lb Axles 21KTR: (3) 7,000 lb Axles w/Easy Lube Spindles, Slipper Spring Suspension. 24KD: (2) 12,000 lb Axle, Dually w/Oil Bath Hubs, Slipper Spring Suspension
Tires:	ST235/80R16 LRE Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable Gooseneck Coupler
Jack:	(2) 12,000 lb Drop Leg Jack
Ramps:	5' Full Width Ramps
Deck Height:	36"
Frame:	12" @ 22 lbs. Heavy Wide-Flange Beams. Crossmembers every 16".
Floor:	Pressure Treated Wood
Gooseneck Length:	9'
Beavertail:	5' Angle Iron Beavertail
Tie Downs:	Stake Pockets & Rub Rails
Side Steps:	On Both Sides
Winch Track:	Driver's Side
Spare Tire Mount:	On Gooseneck
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard

Models

GNFT25-14K	102" x 300"	2,786 kg (6,129 lbs)
GNFT28-14k	102" x 336"	2,946 kg (6,481 lbs)
GNFT30-14K	102" x 360"	3,285 kg (7,227 lbs)
GNFT32-14K	102" x 384"	3,418 kg (7,519 lbs)
GNFT25-21KTR	102" x 300"	3,115 kg (6,854 lbs)
GNFT28-21KTR	102" x 336"	3,415 kg (7,514 lbs)
GNFT30-21KTR	102" x 360"	3,608 kg (7,938 lbs)
GNFT32-21KTR	102" x 384"	3,755 kg (8,260 lbs)
GNFT25-24KD	102" x 300"	3,424 kg (7,533 lbs)
GNFT28-24KD	102" x 336"	3,605 kg (7,930 lbs)
GNFT30-24KD	102" x 360"	3,722 kg (8,190 lbs)
GNFT32-24KD	102" x 384"	3,829 kg (8,424 lbs)

Popular Options

Aluminum Wheels, Not Available on 16K & 24KD	Torsion Axles, Not Available on 24KD
King Pin	Hydraulic Brakes
Spare Tire	D-Rings
16K – Two 8K Axles	Galvanize Trailer
30KD-Two 15K Axles	

Dealer Information & Pricing





Gooseneck XD Series Trailers



Standard Features & Specifications

GVWR:	24KD: 11,757 kg (25,920 lbs) 30KD: 13,636 kg (30,000 lbs)
Axle(s) & Suspension:	24KD: (2) 12,000 lb Axles, Dually 30KD: (2) 15,000 lb Axles, Dually w/Oil Bath Hubs, Hutch Suspension
Tires:	24KD: ST235/80R16 LRE Radial 30KD: ST215/75R15 LRH Radial
Brakes:	Electric on All Axles
Coupler:	Adjustable Gooseneck Coupler
Jack:	12,000 lb 2 Speed Jacks
Ramps:	5' Full Width Ramps
Deck Height:	36"
Frame:	12" @ 22 lbs. Wide Flange Pierced I-Beam Frame. Torque Tube. Crossmembers every 16". HD 1/4" Plate over Axles.
Floor:	Pressure Treated Wood
Gooseneck Length:	9'
Beavertail:	5' Angle Iron Beavertail
Tie Downs:	Stake Pockets & Rub Rails
Side Steps:	On Both Sides
Winch Track:	Driver's Side
Spare Tire Mount:	On Gooseneck
Loading Lights:	Rear Facing w/ Remote On/Off
Lights:	Transport Canada & DOT Approved, Sealed Beam LED
Electrical/Plug:	Sealed Harness & 7 Way RV Plug
Finish:	Powder Coat & Scorpion Stone Guard


Models

GNXD30-24KD	102" x 360"	3,989 kg (8,775 lbs)
GNXD32-24KD	102" x 384"	4,205 kg (9,251 lbs)
GNXD35-24KD	102" x 420"	4,375 kg (9,624 lbs)
GNXD40-24KD	102" x 480"	4,750 kg (10,450 lbs)
GNXD30-30KD	102" x 360"	4,086 kg (8,990 lbs)
GNXD32-30KD	102" x 384"	4,243 kg (9,335 lbs)
GNXD35-30KD	102" x 420"	4,720 kg (10,384 lbs)
GNXD40-30KD	102" x 480"	4,932 kg (10,850 lbs)

Popular Options

King Pin	Hydraulic Brakes
Spare Tire	

Dealer Information & Pricing





CANADA TRAILERS

Canada Trailers Manufacturing Limited

11918 Imperial Road, Hwy. 73
Aylmer Ontario
N5H 2R3

Phone: 519-765-1717

Fax: 519-765-1725

www.canadatrailers.com